The City of Waltham



Invites Interested Parties To propose the best offer and or bid For the service or product herewith described:

STREET PAVING AND REPAIRS TO SIDEWALKS

The bid opening will be held: Wednesday August 28, 2013 at 1:00 pm

Pre-Bid meeting: Wednesday August 21, 2013 at 10:00 am.

Government Center Auditorium 119 School Street,

Waltham, MA

Last Day for written questions: 12 noon Thursday August 22, 2013

Chapter 90 funded projects with a value of \$50,000 or greater: abject to the requirements of Chapter 29 Section 8B of the Massach eneral Laws, each prospective bidder proposing to bid on work to be award municipality under the provisions of section 34 chapter 90 must be prequated accordance with 720 CMR 5.00, "Prequalification of Contractors." The contrust present this approval form to the Chief Procurement Officer at the time pre-bid meeting.		Note:
eneral Laws, each prospective bidder proposing to bid on work to be award municipality under the provisions of section 34 chapter 90 must be prequa accordance with 720 CMR 5.00, "Prequalification of Contractors." The cont ust present this approval form to the Chief Procurement Officer at the ti		Chapter 90 funded projects with a value of \$50,000 or greater:
ease provide the information requested on page 3-8 (a & b) and fill out the page 3-9. Bring both of these two sheets at the time of the pre-bid Meeting Wednesday August 21, 2013	ontractor e time of the form	accordance with 720 CMR 5.00, "Prequalification of Contractors." The just present this approval form to the Chief Procurement Officer at the pre-bid meeting. The pre-bid meeting approval form to the Chief Procurement Officer at the pre-bid meeting. The pre-bid meeting approval form to the Chief Procurement Officer at the pre-bid meeting.

ANNUAL CONTRACT FOR STREET PAVING AND REPAIRS TO SIDEWALKS IN WALTHAM, MASSACHUSETTS

TABLE OF CONTENTS

1.	Invitation to Bid	.1-1 to 1-2
2B.	City of Waltham and Federal AA/EEO requirements and labor standards, including wage rates	Section 2B.
3.	Bid	.3-1 to 3-9
4.	Contract	.4-1 to 4-2
5.	Performance & Payment Bonds	.5-1 to 5-5
6.	General Specifications	.6-1 to 6-9
7.	Technical Provisions	.7-1 to 7-50
8.	Miscellaneous Detail Drawings and documents	Section 8

1 - INVITATION TO BID

FOR

ANNUAL CONTRACT FOR

STREET PAVING AND REPAIRS TO SIDEWALKS

IN

WALTHAM, MASSACHUSETTS

SEALED BIDS for ANNUAL CONTRACT FOR STREET PAVING AND REPAIRS TO SIDEWALKS will be received by Joseph Pedulla, Chief Procurement Officer, City Hall, 610 Main street Waltham, Massachusetts until 1:00 PM EDT, Wednesday August 28, 2013 at which time they will be publicly opened and read.

BIDS shall be received only on the Bid forms provided, properly filled out and placed in a sealed envelope addressed to the Purchasing Agent, Waltham, Massachusetts, and endorsed "BID FOR ANNUAL CONTRACT FOR STREET PAVING AND REPAIRS TO SIDEWALKS" along with the bidder's name.

No Bid will be received unless accompanied by cash or treasurer's check issued by a responsible bank or trust company, or a bid bond for the sum of five percent of the CONTRACTOR'S bid price in favor of the City of Waltham. Should the Bidder selected as the CONTRACTOR on any such work fail to execute the Contract within five days, Sundays and holidays excluded, from the date of mailing a notice to the undersigned at the address given below that the contract is ready for signature, the amount so received as a bid deposit from such bidder through his cash or treasurer's check issued by a responsible bank or trust company, or bid bond shall become and be the property of the said City of Waltham as liquidated damages; provided, that in the case of death, disability or other unforeseen circumstances affecting the bidder, such bid deposit may be returned to him. An award shall then be made to the next lowest responsible and eligible bidder thereon.

The right is reserved by the City of Waltham to reject any or all bids as may be deemed best for the interests of the City and the City of Waltham reserves the right to waive any informalities in the bidding.

The successful bidder will be required to furnish a performance bond and labor and materials payment bond of an approved surety company in an amount not less than the full amount of the Contract.

Specifications and blank Bid forms may be obtained at no charge by visiting the City of Waltham web site at www.city.waltham.ma.us/open-bids.

The successful bidder will be required to furnish a Certificate of Insurance, naming the City as Additional Insured, for General Liability and Vehicle Liability in the amount of \$1,000,000 per occurrence and \$1,000,000 in the aggregate and Worker's Compensation Insurance as prescribed by law.

Attention is called to the fact that minimum wage rates are established for the project as set forth in the Contract documents.

The City of Waltham Supplemental Equal Employment Opportunity, Anti-discrimination and Affirmative Action Program, including special provisions for participation by minority and women business enterprises, applies to this invitation for bids. The bidder's certification form must be signed by all bidders and submitted with each bid.

All bidders are hereby notified that the City of Waltham Affirmative action requirements portion of these documents must be filled out prior to the award of the contract. They will be found in section 2B of these documents.


The successful bidder shall observe faithfully all statutory requirements and local ordinances.

The City of Waltham specifically reserves the right to delete from the Contract any of the items stipulated in the Bid should, in its opinion, such action be necessary. The City of Waltham further reserves the right, should funds be available, to add to the items stipulated in the Bid should, in its opinion, such actions be in the best interest of the City of Waltham.

The responding bidder recognizes receipt of Addenda Number: ____, ____, ____, ____, ____.

Please note that this is a **prevailing wages project**. The prevailing wage schedule is on line at www.city.waltham.ma.us/open-bids. The Contractor is required to submit to the Purchasing Department Office weekly Certified Payrolls and affidavits.

These specifications include a complete set of bid forms which are for the convenience of the bidder and are not to be filled out, executed, or detached from these specifications. Separate copies of the bid forms are furnished for submitting bids.



SECTION 2B

CITY OF WALTHAM AND FEDERAL EQUAL OPPORTUNITY AND AFFIRMATIVE ACTION REQUIREMENTS

INCLUDING WAGE RATES (www.city.waltham.ma.us/open-bids)

The City Of Waltham Equal Employment Opportunity And Affirmative Action Policy

The City of Waltham is committed to a policy of equal employment opportunity and to a program of affirmative action in order to fulfill that policy. The City will accordingly recruit and hire into all positions the most qualified persons in light of job-related requirements, and applicants and employees shall be treated in employment matters without regard to unlawful criteria including race, color, religion, ancestry, national origin, sex, sexual orientation, disability, age, positive HIV-related blood test results, status as a disabled or Vietnam Era Veteran, genetic information, or gender identity or expression, as these terms are defined under applicable law, or any other factor or characteristic protected by law.

In addition, The City of Waltham recognizes that discriminatory harassment and sexual harassment are forms of unlawful discrimination, and it is, therefore, the policy of the City of Waltham that discriminatory harassment and sexual harassment will not be tolerated. The City of Waltham also prohibits unlawful harassment on the basis of other characteristics protected by law.

Further, employees and applicants will not be subjected to harassment or retaliation because they have engaged in or may engage in the following: filing a complaint or assisting or participating in an investigation regarding alleged discrimination or harassment as prohibited in the policy statement above; filing a complaint or assisting or participating in an investigation, compliance evaluation, or any other activity related to the administration of the Vietnam Era Veterans' Readjustment Assistance Act of 1974 ("VEVRAA"), Section 503 of the Rehabilitation Act of 1973 ("Rehabilitation Act"), or the Affirmative Action provisions of federal, state or local law; opposing any act or practice made unlawful by VEVRAA requiring equal employment opportunities for individuals with disabilities, disabled veterans, or veterans of the Vietnam Era; or exercising any rights under VEVRAA or the Rehabilitation Act.

<u>Sources</u>: Titles VI and VII of the Civil Rights Act of 1964; the Immigration Reform and Control Act of 1986; Title IX of the Education Amendments of 1972; the Equal Pay Act of 1963; the Age Discrimination in Employment Act of 1967; the Age Discrimination Act of 1975; Sections 503 and 504 of the Rehabilitation Act of 1973; the Americans with Disabilities Act of 1990; Section 402 of the Vietnam-Era Veterans Readjustment Assistance Act of 1974; Executive Order 11246 as amended; The Genetic Information Nondiscrimination Act of 2008 and such other federal, state and local non-discrimination laws as may apply.

3 - BID
FOR
ANNUAL CONTRACT FOR
STREET PAVING AND REPAIRS TO SIDEWALKS
IN
WALTHAM, MASSACHUSETTS

TO: Mr. Joseph Pedulla, Chief Procurement Officer CITY OF WALTHAM, MASSACHUSETTS

The undersigned, as bidder, hereby declares that he has carefully examined the specifications and provisions attached hereto, and that he proposes and agrees, if this Bid is accepted, that he will contract with the CITY OF WALTHAM in the form prescribed for the ANNUAL CONTRACT FOR STREET PAVING AND REPAIRS TO SIDEWALKS as herein specified and will provide therefore all necessary materials, labor, machinery and equipment, and will perform all the work in the manner prescribed and according to the requirements of the OWNER.

Accompanying this Bid is cash or a treasurer's check payable to the City of Waltham, or a Bid bond in the amount of five percent of the CONTRACTOR'S Bid price

If this Bid shall be accepted and the undersigned shall fail to execute the required contract, in accordance with the terms herein set forth, within five days from the date of mailing a notice to the undersigned at the address given below that the contract is ready for signature, the City of Waltham may, at its option, determine that this Bid shall be null and void, and the aforesaid cash or checks shall become the property of the City of Waltham; otherwise the said cash or checks shall be returned to the undersigned.

BIDDER ACKNOWLEDGES RECEIPT OF THE FOLLOWING ADDENDA:	
	_

The undersigned, as Bidder, hereby declares that he will take full payment thereof sums based on the following unit prices as applied to the various quantities ordered by the OWNER from time to time during the life of this contract.

103.000	10 EACH	TREE REMOVED (DIAMETER UNDER 24 INCHES	Unit Price	Extended Price
		PER EACH PER EACH		
104.000	10 EACH	TREE REMOVED (DIAMETER OVER 24 INCHES)	Unit Price	Extended Price
		– PER EACH		
105.000	20 EACH	STUMP REMOVED	Unit Price	Extended Price
		PER EACH		
120.100	4,000	UNCLASSIFIED EXCAVATION	Unit Price	Extended Price
	CY	PER CY		
		CEMENT CONCRETE EXCAVATION	Unit Price	Extended Price
127.000	2,200			
	SY	PER SY		
420.040	20.000	COLD PLANING	Unit Price	Extended Price
129.010	30,000 SY	PER SY		
	31		Heit Deiss	Futon dod Drice
151.220	200	GRAVEL BORROW FOR SIDEWALKS	Unit Price	Extended Price
131.220	CY	PER CY		
		CRUSHER RUN	Unit Price	Extended Price
151.900	1,000			
	TN	PER TON		
		SAND FOR RECLAMATION	Unit Price	Extended Price
154.001	200 TN			
	TN	PER TON	Harte Balan	Estanded Dife
220.000	300	DRAINAGE STRUCTURE ADJUSTED	Unit Price	Extended Price
220.000	EA	EACH		
		DRAINAGE STRUCTURE REMODELED	Unit Price	Extended Price
220.500	200		2	
	VF	PER VERTICAL FOOT		
		FRAME AND GRATE OR COVER (IN PLACE)	Unit Price	Extended Price
222.010	50			
	EA	EACH		
		6" SERVICE GATE BOX	Unit Price	Extended Price
357.060	100			
	EA	EACH		

358.100	200	SIDEWALK GATE BOX ADJUSTED	Unit Price	Extended Price
	EA	EACH		
358.200	300	ROADWAY GATE BOX ADJUSTED	Unit Price	Extended Price
	EA	EACH		
403.001	95,000	ROADWAY RECLAMATION AND EXCAVATION	Unit Price	Extended Price
	SY	PER SQUARE YARD		
405.000	200	TRENCH REPAIR	Unit Price	Extended Price
	SY	PER SQUARE YARD		
440.000	4,000	CALCIUM CHLORIDE FOR DUST CONTROL	Unit Price	Extended Price
	LB	PER POUND		
460.000	20,000	CLASS I BITUMINOUS CONCRETE (TYPE I-1) (ROADWAY)	Unit Price	Extended Price
	TN	PER TON		
460.100	3,500 TN	CLASS I BITUMINOUS CONCRETE (TYPE I-1) (SIDEWALKS, DRIVES, PERMANENT PATCHING)	Unit Price	Extended Price
		PER TON		
460.300	10,000	CLASS I BITUMINOUS CONCRETE (TYPE I-1) (ROADWAY NIGHT WORK)	Unit Price	Extended Price
	TN	PER TON		
464.000	6,000	BITUMEN FOR TACK COAT	Unit Price	Extended Price
404.000	GL	PER GALLON		
470.000	12,000	BITUMINOUS CONCRETE CURB (TYPE 2)	Unit Price	Extended Price
., 0.000	LF	PER LINEAR FOOT		
504.000	8,000	GRANITE CURB TYPE VA-4 (STRAIGHT)	Unit Price	Extended Price
	LF	PER LINEAR FOOT		
504.100	4,000	GRANITE CURB TYPE VA-4 (CURVED)	Unit Price	Extended Price
	LF	PER LINEAR FOOT		

514.000	40 EACH	GRANITE CURB INLET-STRAIGHT	Unit Price	Extended Price
	27.01.	PER EACH		
515.000	20 EACH	GRANITE CURB INLET-CURVED	Unit Price	Extended Price
	E/ (C/)	PER EACH		
		GRANITE CURB CORNER TYPE A (2' RADIUS)	Unit Price	Extended Price
516.000	50			
	EA	EACH		
		GRANITE CURB CORNER TYPE B (3' RADIUS)	Unit Price	Extended Price
517.000	10			
	EA	EACH		
520.000	3,000 LF	CONCRETE CURB –STRAIGHT	Unit Price	Extended Price
	Li	PER LINEAR FOOT		
520.100	1,500	CONCRETE CURB –CURVED	Unit Price	Extended Price
	LF			
		PER LINEAR FOOT		
		CURB REMOVE AND RESET	Unit Price	Extended Price
580.000	4,500			
	LF	PER LINEAR FOOT		
		4" CEMENT CONCRETE SIDEWALK FIBER MESH REINFORCED	Unit Price	Extended Price
701.050	4,000 SY	PER SQUARE YARD		
	31	6" CEMENT CONCRETE SIDEWALK FIBER MESH REINFORCED	Unit Price	Extended Price
701.150	1,500	O CEIVIEW CONCRETE SIDEWALK TIDEN WIEST KEIW ONCED	Office	Extended Frice
	SY	PER SQUARE YARD		
		STONE BOUND REMOVED AND RESET	Unit Price	Extended Price
711.000	8			
	EA	EACH		
		STONE BOUND FRAME AND COVER	Unit Price	Extended Price
711.100	8			
	EA	EACH		
751.000	1,000	LOAM BORROW	Unit Price	Extended Price
/31.000	1,000 CY	PER CUBIC YARD		
	-	SEEDING	Unit Price	Extended Price
765.000	10,000			
	SY	PER SQUARE YARD		

765.650	10,000 SY	HYDRO SEEDING	Unit Price	Extended Price
		PER SQUARE YARD		
801.300	500	3" TRAFFIC CONDUIT	Unit Price	Extended Price
	LF	PER LINEAR FOOT		
819.837	1,000	LOOP DETECTORS WITH LEAD-IN WIRES	Unit Price	Extended Price
	LF	PER LINEAR FOOT		
819.840	10	TRAFFIC CAMERA	Unit Price	Extended Price
010.0	EA	EACH		
819.850	20	TRAFFIC CAMERA RELATED EQUIPMENT	Unit Price	Extended Price
	EA	EACH		
819.860	2,400	SENSOR CABLE FOR TRAFFIC CAMERAS	Unit Price	Extended Price
	LF	PER LINEAR FOOT		
850.221	3,000	SAFETY SIGNING FOR CONSTRUCTION OPERATIONS	Unit Price	Extended Price
	SF	PER SQUARE FOOT		
854.014	1,200	TEMPORARY PAVEMENT MARKINGS – 4" PAINTED	Unit Price	Extended Price
	LF	PER LINEAR FOOT		
864.040	1,500 SF	PAVEMENT ARROWS AND LEGENDS REFLECTORIZED WHITE THERMOPLASTIC	Unit Price	Extended Price
	31	PER SQUARE FOOT		
865.100	5,000 SF	CROSSWALKS AND STOP LINES REFLECTORIZED WHITE THERMOPLASTIC	Unit Price	Extended Price
		PER SQUARE FOOT		
868.040	20,000 LF	4" WHITE OR YELLOW REFLECTIVE THERMOPLASTIC LINE	Unit Price	Extended Price
		PER LINEAR FOOT		
870.000	250	PORTABLE MESSAGE BOARD	Unit Price	Extended Price
670.000	250 DY	PER DAY		

		TRAFFIC POLICE		
999.001	200,000 \$\$	DOLLAR FOR DOLLAR REIMBURSEMENT	\$1.00	\$200,000
			Total Bid pri	ce in figures:
Total Bid _I	orice wri	tten in words:	\$	

It is understood and agreed that the quantities set forth in the Bid are provided for bid comparison only and the actual quantity of work to be done may vary, as determined by the OWNER. The CONTRACTOR agrees that he shall neither have nor assert any claim for or be entitled to any additional compensation for damages or for loss of anticipated profits on work that is eliminated.

The time for completion of work under this contract shall be one year from the date of the Notice to Proceed. The City of Waltham, at its sole option, may elect to extend the contract period for an additional year.

All unit prices quoted herein shall be firm for the duration of this Contract, regardless of any changes in the cost of materials and labor, with the exception of hot mix asphalt (HMA) mixtures, diesel fuel and gasoline, and Portland cement concrete mixtures. For monthly price adjustments for these items, refer to Mass Highway documents 00811, 00812 and 00814 respectively. Copies of these documents are included in section 8.

In accordance with Massachusetts General Laws, the undersigned certifies that the bidder has filed all state tax returns and paid all state taxes required by law.

In accordance with Massachusetts General Laws, the undersigned certifies that all employees to be employed at the worksite will have successfully completed a course in construction safety and health approved by OSHA that is at least 10 hours in duration at the time the employee begins work and shall furnish documentation of successful completion of said course with the first certified payroll report for each employee.

This is a project expected to last **Two (2) years**; therefore the contract between the company and the City is for a Two (2) year Period.

No new paving will start after October 15 unless by the authorization of the Mayor via signed Change Order.

BIDDER	
SIGNATURE	
BUSINESS ADDRESS	
 TELEPHONE NUMBER	
TELEPHONE NOWIBER	
FAX NUMBER	
EMAIL ADDRESS	
DATE	
Bidder must read pages 2-17, 3-8 and 3	3-9, and submit pages 2-17 and 3-9 filled out in their entirety with the Bid.
Bidder must read pages 2-17, 3-8 and 3	3-9, and submit pages 2-17 and 3-9 filled out in their entirety with the Bid.
Bidder must read pages 2-17, 3-8 and :	3-9, and submit pages 2-17 and 3-9 filled out in their entirety with the Bid.
Bidder must read pages 2-17, 3-8 and	3-9, and submit pages 2-17 and 3-9 filled out in their entirety with the Bid.
Bidder must read pages 2-17, 3-8 and	3-9, and submit pages 2-17 and 3-9 filled out in their entirety with the Bid.
Bidder must read pages 2-17, 3-8 and	3-9, and submit pages 2-17 and 3-9 filled out in their entirety with the Bid.
Bidder must read pages 2-17, 3-8 and	3-9, and submit pages 2-17 and 3-9 filled out in their entirety with the Bid.
Bidder must read pages 2-17, 3-8 and	3-9, and submit pages 2-17 and 3-9 filled out in their entirety with the Bid.

PROOF OF CONTRACTOR'S RESPONSIBILITY

Before a contract will be awarded to any Bidder, he will be required to furnish evidence satisfactory to the OWNER that he has all of the following qualifications:

- **A**. Ability, equipment, organization, and financial resources sufficient to enable him to construct and complete the work successfully within the time required.
- **B.** Experience during the past three years in the successful construction of similar engineering projects, the magnitude of which shall be not less than one-half the work herein specified. In this connection, the attention of the Bidder is directed to the Bidder's experience form attached, that shall be used in determining the responsibility of the Bidder. The OWNER may require additional information whenever, in his judgment, such information is necessary to determine the responsibility of the Bidder.

An experienced Bidder shall be construed to mean that the Bidder has a minimum of three individuals within his organization that have the experience to supervise a job of this nature and magnitude. Their experience shall include previous work of a nature similar to the work prescribed in this contract.

In the event the Bidder fails, refuses, or neglects to submit any required information within the reasonable time stated in any request or fails to qualify as a responsible Bidder, his Bid guaranty shall be forfeited to the use of the OWNER, not as a penalty, but as liquidated damages.

The determination of whether a Bidder is responsible shall rest solely with the OWNER.

BIDDER'S EXPERIENCE
The following is a list of the projects similar in character and scope to the work specified in this contract that have been successfully completed by this Bidder during the past three years. "Completed" means the OWNER or authorized representative has accepted the project and final payment has been received. Each Bidder must furnish this information. If provided in a different format, all of the following information must be included.
LOCATION TYPE OF WORK DOLLAR VALUE OWNER'S NAME AND ADDRESS OWNER'S ENGINEER AND PHONE DATE COMPLETED
BIDDER'S SIGNATURE

4 - CONTRACT
FOR
ANNUAL CONTRACT FOR
STREET PAVING AND REPAIRS TO SIDEWALKS
IN
WALTHAM, MASSACHUSETTS

CLAUSE 1. This agreement is made this	day of	in the year Two Thousand
Thirteen by and between the City of Waltham, party o	of the first part, hereinafter	called the CITY, by its MAYOR, and
party of the second part, hereinafter called the CONTR	ACTOR	
party of the second party herematter canca the second		

CLAUSE 2. Witnesseth, that the parties to this agreement, each in consideration of the agreement on the part of the others herein contained, do hereby agree, the City of Waltham for itself, and said CONTRACTOR for his heirs, executors, administrators and assigns as follows:

The CONTRACTOR agrees to furnish all equipment, machinery, tools and labor, to furnish and deliver all materials required to be furnished (except as otherwise specified) and deliver in and about the project and to do and perform all work in ANNUAL CONTRACT FOR RESURFACING OF BITUMINOUS ROADWAYS AND REPAIRS TO SIDEWALKS and in strict conformity with the provisions of this contract and of the INVITATION TO BID, Bid and specifications hereto annexed. The said specifications and INVITATION TO BID are hereby made a part of this contract as fully and to the same effect as if the same had been set forth at length and incorporated in the contracts.

CLAUSE 3. In consideration of the foregoing promises the CITY agrees to pay and the CONTRACTOR agrees to receive as full compensation for everything furnished and done by the CONTRACTOR under this contract, including all work required but not included in the items herein mentioned, and for any unforeseen obstruction or difficulty encountered in the prosecution of the work, and for well and faithfully completing the work, and the whole thereof, as herein provided, such prices as are set forth in the accompanying bid.

CLAUSE 4: The time for completion of work under this contract shall be one year from the date of the Notice to Proceed. The City of Waltham, at its sole option, may elect to extend the contract period for an additional year.

It is understood and agreed that the quantities set forth in the Bid are approximate and the actual quantity of work to be done may be more or less, as determined by the OWNER. The CONTRACTOR agrees that he shall neither have nor assert any claim for or be entitled to any additional compensation for damages or for loss of anticipated profits on work that is eliminated.

	BY MAYOR	DAT
	APPROVED AS	TO FORM ONL
	CITY SOLICITOR	DAT
FOR THE COMPANY	BY CHIEF PROCUREMENT OFFICER	DAT
SIGNATURE, TITLE AND SEAL		
	BY CITY AUDITOR	DAT
	Bremnobnon	57.
	BY CPW ACTING DIRECTOR	DA

5A - PAYMENT BOND
FOR
ANNUAL CONTRACT FOR
RESURFACING OF BITUMINOUS ROADWAYS AND REPAIRS TO SIDEWALKS
IN
WALTHAM, MASSACHUSETTS

KNOW ALL MEN BY THESE PRESENT, THAT	
	AS PRINCIPAL AND
	AS SURETY
are held and firmly bound unto the CITY OF WALTHAM furnish materials for or perform labor on the work, conhereinafter mentioned, or who may have any suits or cla from or arising out of the work done under this Contract,	struction or improvements contemplated in the Contrac
IN THE SUM OF	payment whereof the CONTRACTOR and the Surety o
THE CONDITION OF THIS OBLIGATION IS SUCH, that if the a	above bounden

heirs, executors, administrators and assigns, shall promptly make payment to all persons, firms, subcontractors, and corporations furnishing materials for or performing labor in the prosecution of the work provided for in ANNUAL CONTRACT FOR RESURFACING OF BITUMINOUS ROADWAYS AND REPAIRS TO SIDEWALKS and any authorized extensions or modification thereof, including all amounts due for materials, lubricants, oil, gasoline, repairs on machinery, equipment and tools consumed or used in connection with the construction of such work, and all insurance premiums on said work, and for all labor performed in such work, whether by subcontractors or otherwise, then this obligation shall be void; otherwise to remain in full force and effect,

PROVIDED, HOWEVER, that (except as to the OWNER) no suit, action or proceeding by reason of any default whatever shall be brought on this Bond after two years from the day on which the final payment under the Contract falls due,

AND PROVIDED, that any alterations that may be made in the terms of the Contract or in the work to be done under it, or any assignment, transfer or subletting of any part of the work, or the giving by the OWNER of any extension of

time for the performance of the Contract, or any other forbearance on the part of either the OWNER or the CONTRACTOR to the other, shall not in any way release the CONTRACTOR and the Surety or Sureties, or either or any of them, their heirs, executors, administrators, successors or assigns from their liability hereunder, notice to the Surety or Sureties of any such altercations, assignment, transfer, subletting, extension or forbearance being hereby waived.

This Bond is made for the use and benefit of all persons, firms, and corporations who may furnish materials, or perform any labor for or on account of said work, construction or improvements, or who may have any suits or claims for injury or damage to persons or property resulting from or arising out of the work done under this Contract, and they and each of them are hereby made obligees hereunder the same as if their own proper names were written herein as such, and they and each of them may sue hereon in their own names for their own use and benefit.

And the Surety, for value received, hereby stipulates and agrees that no change, extension of time, alteration or addition to the terms of the Contract or to the work to be performed hereunder, or the Specifications accompanying the same, shall in any way affect its obligations on this Bond, and it does hereby waive notice of any such changes, extension or time, alteration or addition to the terms of the Contract or to the work, or to the Specifications.

IN WITNESS WHEREOF, Said CONTRAC	TOR and Surety have hereunto set t	their respective names
this	day of	
WITNESSES:	_	CONTRACTOR (SEAL)
NAME	BY	SIGNATURE AND TITLE
ADDRESS	BY	SURETY (SEAL)
NAME	BY	SIGNATURE AND TITLE
ADDRESS	BY	ATTORNEY-IN-FACT

<u>POWER OF ATTORNEY:</u> Attorneys-in-fact who sign contract bonds must file with each bond a certified copy of their power of attorney to sign said bonds.

5B - PERFORMANCE BOND
FOR
ANNUAL CONTRACT FOR
RESURFACING OF BITUMINOUS ROADWAYS AND REPAIRS TO SIDEWALKS
IN
WALTHAM, MASSACHUSETTS

KNOW ALL MEN BY THESE PRESENT, THAT		
		AS PRINCIPAL AND
	AS 9	SURETY
are held and firmly bound unto the CITY OF WALTHAM and to materials for or perform labor on the work, construction or impor- mentioned, or who may have any suits or claims for injury or dark out of the work done under this Contract	rovements contemplated in the C	Contract hereinafter
IN THE SUM OF	DOLLARS (\$)
(lawful money of the United States of America) for the paym Sureties bind themselves and their heirs, executors, administrative firmly by these presents.		•
THE CONDITION OF THIS OBLIGATION IS SUCH, that if the above	bounden	
heirs, executors, administrators and assigns, shall faithfully po	erform the Contract for ANNUA	AL CONTRACT FOR

heirs, executors, administrators and assigns, shall faithfully perform the Contract for ANNUAL CONTRACT FOR RESURFACING OF BITUMINOUS ROADWAYS AND REPAIRS TO SIDEWALKS on his part and during the life of any guaranty or warranty, including warranty for defective materials and workmanship required under this Contract, and satisfy all claims and demands incurred for the same; and shall fully indemnify and save harmless the OWNER from all costs and damage that it may suffer by reason of failure so to do, and shall fully reimburse and repay the OWNER all outlay and expense that the OWNER may incur in making good any such default, and shall promptly make payment to all persons supplying labor or materials for use in the prosecution of the work provided for in said Contract; and shall indemnify and save harmless the said OWNER, its officers and agents from any and all suits or claims for injury or damage to persons or property resulting from or arising out of the work done under this Contract, then this obligation shall be null and void; otherwise it shall remain in full force and effect,

PROVIDED, HOWEVER, that (except as to the OWNER) no suit, action or proceeding by reason of any default whatever shall be brought on this Bond after two years from the day on which the final payment under the Contract falls due,

AND PROVIDED, that any alterations that may be made in the terms of the Contract or in the work to be done under it, or any assignment, transfer or subletting of any part of the work, or the giving by the OWNER of any extension of time for the performance of the Contract, or any other forbearance on the part of either the OWNER or the CONTRACTOR to the other, shall not in any way release the CONTRACTOR and the Surety or Sureties, or either or any of them, their heirs, executors, administrators, successors or assigns from their liability hereunder, notice to the Surety or Sureties of any such alterations, assignment, transfer, subletting, extension or forbearance being hereby waived.

This bond is made for the use and benefit of all persons, firms and corporations who may furnish materials, or perform any labor for or on account of said work, construction or improvements, or who may have any suits or claims for injury or damage to persons or property resulting from or arising out of the work done under this Contract, and they and each of them are hereby made obligees hereunder the same as if their own proper names were written herein as such, and they and each of them may sue hereon in their own names for their own use and benefit.

And the Surety, for value received, hereby stipulates and agrees that no change, extension of time, alteration or addition to the terms of the Contract or to the work to be performed hereunder, or the Specifications accompanying the same, shall in any way affect its obligations on this Bond, and it does hereby waive notice of any such changes, extension of time, alteration or addition to the terms of the Contract or to the work, or to the Specifications.

IN WITNESS WHEREOF, said CONTRACTOR and Surety have hereunto set their respective names

this	_ day of	
<u>WITNESSES</u> :		
		CONTRACTOR (SEAL)
NAME	BY	
		SIGNATURE AND TITLE
ADDRESS	BY	
		SURETY (SEAL)
NAME	BY	
		SIGNATURE AND TITLE
ADDRESS	BY	
		ATTORNEY-IN-FACT

<u>POWER OF ATTORNEY</u>: Attorneys-in-fact who sign contract bonds must file with each bond a certified copy of their power of attorney to sign said bonds.

5C - ATTESTATION
FOR
ANNUAL CONTRACT FOR
STREET PAVING AND REPAIRS TO SIDEWALKS
IN
WALTHAM, MASSACHUSETTS

Pursuant to Massachusetts General Laws Chapter 62C Section 49A, I certify under the penalties of perjury that I, to the best of my knowledge and belief, have filed all Massachusetts tax returns and paid all Massachusetts taxes required under law. *

Signature of CONTRACTOR	
Name of CONTRACTOR (Agency)	
Federal Identification Number or Social Security Number	

^{*} Legislation enacted by the Commonwealth of Massachusetts, effective July 1, 1983, requires that all contractors doing business with municipalities sign the above Attestation.

6 - SPECIFICATIONS
FOR
ANNUAL CONTRACT FOR
STREET PAVING AND REPAIRS TO SIDEWALKS
IN
WALTHAM, MASSACHUSETTS

1) GENERAL PROVISIONS

- (a) The attention of the CONTRACTOR is called to the provisions of MGL Chapter 149, §6: that in the employment of mechanics, teamsters and laborers, preference shall first be given to citizens of the Commonwealth of Massachusetts who have served in the Armed Forces of the United States in time of war and have been honorably discharged therefrom, or released from active duty therein, and who are qualified to perform the work, to which the employment relates, and secondly, to citizens of the Commonwealth of Massachusetts generally and if they cannot be obtained in sufficient numbers, then to citizens of the United States: that no laborer, workman or mechanic working within the Commonwealth of Massachusetts in the employ of the CONTRACTOR, subcontractor or other person doing or contracting to do the whole or any part of the work contemplated by this agreement shall be requested to work more than eight hours in any one day, or shall be requested or required to work more than forty hours any one week, except in cases of extraordinary emergency, and that the CONTRACTOR will in all things, observe and comply with any and all other provisions of law relative to agreements or contracts for the performance of public work.
- (b) The CONTRACTOR shall do all the work and furnish all the labor, materials, implements, tools, machinery and applications, except as herein otherwise specified, necessary or proper for performing and completing the work required by this contract in the manner herein specified.
- (c) All the work, labor and materials to be done and furnished under this contract shall be done and furnished strictly pursuant to and in accordance with the directions of the OWNER as given from time to time during the progress of the work under the terms of this contract.
- (d) The CONTRACTOR shall complete the entire work in accordance with the specifications for the work and to the satisfaction of the OWNER.
- (e) The INVITATION TO BID and the BID submitted by the CONTRACTOR shall be made parts of this contract.
- (f) The CONTRACTOR, during the progress of the work, shall take every precaution to ensure the absolute safety of the public from injury.
- (g) The CONTRACTOR agrees to give his personal attention to the work or, during his absence, agrees to delegate his authority to a duly authorized agent who shall represent him in the decision of all matters relative to the construction of the work. The CONTRACTOR is to be responsible for any damage to property resulting from his operation.
- (h) The attention of the CONTRACTOR is also called to the provisions relative to directing or requiring employees to lodge, board or trade at any particular place or with any particular person or persons and the CONTRACTOR agrees to be governed by such provisions.

- (i) The CONTRACTOR shall keep himself fully informed as to all laws, bylaws, ordinances, regulations, orders, decrees and wage rates, and shall protect and indemnify the CITY and all its officers, agents and servants against any claim or liability arising from, or based on, the violation of any such all laws, bylaws, ordinances, regulations, orders, decrees and wage rates, whether by himself or his employees or subcontractors.
- (j) The CONTRACTOR agrees to take out and maintain at his own expense insurance against damage arising from injury to his employees, in accordance with MGL Chapter 152 and amendments thereof.

2) **DEFINITIONS**

- (a) "ENGINEER," "CITY ENGINEER," "CPW ASSISTANT DIRECTOR," "CITY" or "OWNER" shall mean the CITY OF WALTHAM, acting directly or through properly authorized agents; such agents acting within the scope of the particular duties entrusted to them.
- (b) The word "CONTRACTOR" shall mean the party or parties contracting to perform the work covered by this contract or his or their legal representative successors or assigns.

3) EXAMINATION OF THE SITE

Before submitting his BID, the CONTRACTOR shall visit the site, examine its condition and thoroughly acquaint himself with the obstacles and advantages of performing the work. He shall also study the plans and specifications explanatory of the work and compare the same with the information gathered by the examination of the site.

4) SITE CONDITIONS

It is expressly understood and agreed that the CITY does not warrant or guarantee that the materials encountered during construction will be the same as the information given on the drawings. The results and descriptions are for the information of the CONTRACTOR, but are not guaranteed. The CONTRACTOR must satisfy himself regarding the character and quantities of the various materials and work to be done. It is further understood and agreed that the Bidder or CONTRACTOR will not use any of the information obtained in such examination in any manner as a basis or ground of claim or demand of any nature against the CITY arising from or by reason of any variance that may exist between the samples examined and described and the actual materials or structures encountered during the construction work.

5) ESTIMATED QUANTITIES

Wherever the estimated quantities of work to be done and materials to be furnished under this Contract are shown in any of the documents, including the BID, they are given for use in comparing Bids. The right is especially reserved to increase or diminish them as may be deemed reasonably necessary or desirable by the OWNER to complete the work contemplated by this CONTRACT, and such increase or reduction shall in no way invalidate this CONTRACT, nor shall any such increase or diminution give cause for claims or liability for damage. CONTRACTOR shall order materials based on actual field measurements and not quantities estimated in the Bid. The City of Waltham will not be responsible for overstocked materials.

6) ITEMS NOT LISTED IN THE BID

The lump sum and unit price items listed in the Bid form are intended to cover all items of work to be done and materials and work to be furnished to fully complete the work in accordance with the Contract Documents. Appurtenant items of work as shown on the Drawings or as specified or as required, and parts of the work, materials, and equipment not listed separately and not shown or specified to complete the work under the item or not shown in the Bid shall be considered as incidental to the applicable item and included in the cost of payment under the various applicable Bid items of work, and no separate payment will be made for such items. It shall be the responsibility of the CONTRACTOR to verify any missing or incomplete data.

7) BALANCED BIDDING

Bids should be made on each separate item of work shown in the BID with reasonable relation to the probable cost of doing the work included in such items, and the right is reserved to reject wholly any Bid where an item or items thereof are obviously unbalanced or appear to the CITY to be so unbalanced as to affect or to be liable to affect adversely any interests of the CITY. The attention of the Bidder is called to the fact that unbalancing of Bids may adversely affect the CONTRACTOR if certain portions of the work are increased or decreased as provided in the paragraph 5).

8) DISCREPANCIES, ERRORS AND OMISSIONS

Drawings and specifications are intended to be explanatory of each other, but should any discrepancy appear or any misunderstanding arise as to the import of anything contained in either, the interpretation and decision of the OWNER shall be final and binding on both parties to this contract. Any correction of error or omissions in drawings and specifications may be made by the OWNER when such correction is necessary for the proper fulfillment of their intention as construed by him. Where said correction of errors or omissions, except as provided in the next two paragraphs below, adds to the amount of work to be done by the CONTRACTOR, compensation for said additional work shall be made under the provision for "Claims for Additional Work," except where the additional work may be classed under some item of work for that a unit price is included in the BID.

The fact that specific mention of a fixture, or any part of the work, is omitted in the specifications, whether intentionally or otherwise, when the same is clearly shown or indicated on the drawings, or is usually and customarily required to complete such work as is specified herein, will not entitle the CONTRACTOR to consideration in the matter of any claim for extra compensation. The said fixtures or work, or both, must be installed or done the same as if called for by both the drawings and the specifications.

Work indicated on the drawings and not mentioned in the specifications or vice versa, and all work and material usual and necessary to make the work complete in all its parts, whether or not indicated on the drawings or mentioned in the specifications shall be furnished and executed the same as if called for by both the drawings and specifications.

9) CLAIMS FOR ADDITIONAL WORK

The CONTRACTOR shall make no claim for additional work or materials unless the same shall be performed or furnished in pursuance of an order from the OWNER and unless the same shall be specifically authorized in writing, signed by the MAYOR. Notice of all claims for additional work and material shall be made to the OWNER in writing ten days from the beginning of such work or the furnishing of such materials.

10) SUBCONTRACTS

No work may be sublet or subcontracted without prior written approval of the OWNER.

11) OWNER TO BE REFEREE

To minimize disputes and litigation, it is further agreed by and between the parties to this contract that the OWNER shall decide all questions arising during the progress of the work and his decisions shall be final and binding upon the parties to this contract.

12) JURISDICTIONAL DISPUTES

It shall be the responsibility of the CONTRACTOR to see that the proper trades perform their respective work.

13) COMPLETION OF THE WORK

- (a) The CONTRACTOR agrees to complete the work hereunder required in every particular in a prompt and diligent manner and to the satisfaction of the OWNER in accordance with the plans, specifications and this contract within the period of the time stated in the BID.
- (b) The MAYOR shall have the right to extend the time for completion of said work but such time shall not be extended except upon application in writing by the CONTRACTOR and good cause shown.
- (c) The time shall be extended if delay is caused by a strike or boycott for which the CONTRACTOR is in no way responsible and which the CONTRACTOR cannot reasonably avoid.
- (d) Neither an extension of time, for any reason beyond that fixed herein for the completion of the work nor the doing and acceptance of any part of the work called for by this contract, shall be deemed to be a waiver by the CITY OF WALTHAM of the right to abrogate this contract for abandonment or delay in the manner provided for in paragraph 14) of this contract.

14) ABANDONMENT OF THE WORK

The CONTRACTOR further agrees that if the work to be done under this contract shall be abandoned, or if the work shall not be fully completed on the day herein specified, or if this contract shall be assigned by the CONTRACTOR otherwise than as herein specified, or if at any time the OWNER shall be of the opinion and shall certify in writing to the MAYOR, that the work is unnecessarily or unreasonably delayed, or that the CONTRACTOR is willfully violating any of the conditions or agreements of this contract, or is not executing said contract in good faith, or is not making such progress in the execution of the contract as to indicate its completion within the required time, the MAYOR shall have the power and the right to notify the CONTRACTOR to discontinue said work or such part thereof as the MAYOR may designate, and the MAYOR shall thereupon have the power and the right to notify the CONTRACTOR to discontinue said work or such part thereof as the MAYOR may designate; and the MAYOR shall thereupon have the power by contract or otherwise as he may determine, to employ such persons and obtain such appliances and tools as he may deem necessary to work at, and be used to complete the work herein described or such part thereof as he may deem necessary and to use such implements and materials of every description as may be found upon the premises both such as enter into the completed work and such as are necessarily used in and about the same in the course of construction, and to procure other materials and implements to the CONTRACTOR; and the expense so charged shall be deducted and paid by the MAYOR out of such money as may be deemed either due at any time thereafter become due to the CONTRACTOR under this contract or any part thereof, and in case such expense is less than the sum that would have been payable under this contract if the same had been completed by the CONTRACTOR, then the CONTRACTOR shall be entitled to receive the difference and in case such expense exceeded

the sum which would have been payable under this contract if the same had been completed by the CONTRACTOR, then the CONTRACTOR shall pay the amount of such excess to the CITY OF WALTHAM.

15) PAYMENT TO THE CONTRACTOR

The OWNER shall, from time to time, certify as to the work done to date and the value thereof, and payment shall be made to the CONTRACTOR on a unit price basis for the work completed to date. The CITY OF WALTHAM shall retain five percent of such value and pay to the CONTRACTOR the balance, after deduction therefrom all previous payments and all sums to be kept or retained under the provisions of previous payments and all sums to be kept or retained under the provisions of this contract. It is further agreed that the sum as herein provided will be paid by the CITY OF WALTHAM and shall be received by the CONTRACTOR as full compensation for furnishing and installing material and executing all the work contemplated by the CONTRACTOR, also for all loss or damage arising out of the nature of the work aforesaid or from the action of the elements or from any unforeseen obstruction or difficulties that may be encountered in the prosecution of the same or from hindrance or delay from any cause whatsoever in the progress of the work and for all risks of every description connected with the work; also for all expenses incurred by or in consequence of the suspension of discontinuance of said work as herein specified and for well and faithfully completing the whole in the manner and in accordance with the plans and specifications and requirements of the OWNER. Ninety five percent of such sum shall be paid by the CITY OF WALTHAM to the CONTRACTOR, it being understood that the final payment be made within sixty days after this contract is completely finished provided that the OWNER shall certify in writing that all the work has been done to his satisfaction, and provided further that nothing herein contained shall be construed to effect the right of the MAYOR hereby reserved, to reject the whole or any portion of the aforesaid work should the certificate be found or known to be inconsistent with the terms of this agreement, or otherwise improperly given and provided further that if at any time there shall be any claim of the sort mentioned in paragraph 16) or paragraph 32) of this contract to the MAYOR, the CITY OF WALTHAM shall have the right to retain out of the payment an amount sufficient to pay such claim until the same shall be satisfied or canceled.

16) UNPAID CLAIMS

The CONTRACTOR further agrees that he will pay all bills for labor and materials contracted for by him on account of the work herein contemplated and that he will furnish the MAYOR at her request with evidence satisfactory to him that all persons who have done work or furnished material under this contract and all claims of private corporations or individuals for damages of any kind, caused by the construction of said work, have been fully paid or satisfactorily secured. The MAYOR shall cause to be retained, out of such amount due the CONTRACTOR, sums sufficient to cover any such unpaid claims.

17) PERMITS

The CONTRACTOR shall obtain all necessary permits for the execution of this contract, including a street opening permit, obtained at no charge from the Consolidated Public Works Department (781) 314-3800.

18) PROSECUTION AND PROGRESS

The CONTRACTOR shall commence work within fifteen days after the mailing of the executed CONTRACT unless otherwise ordered in writing by the OWNER, and the CONTRACTOR shall thereafter prosecute the work at such places and in such order as the OWNER may from time to time prescribe.

Should the prosecution of the work for any reason be discontinued, the CONTRACTOR shall notify the OWNER at least twenty-four hours prior to resumption of operations.

19) SCHEDULE

Within fifteen days after the mailing of the executed CONTRACT, a meeting shall be held between the OWNER and the CONTRACTOR who is awarded the Bid. At this meeting, a schedule of the work to be done shall be set up by the OWNER and the CONTRACTOR. Time schedules for various phases of construction will be determined and compiled in a manner that is satisfactory to both the CONTRACTOR and the OWNER.

20) LINES AND GRADES

The OWNER will establish sufficient points to fix the location, alignment and elevation of the work. The CONTRACTOR will furnish the layout of all parts of the work from the points furnished and shall maintain all such points, lines and grades at no additional cost to the CITY. Finished surfaces, in all cases, shall conform as near as practical to the lines and grades given. The CONTRACTOR shall supply appropriate survey equipment for use by the OWNER to permit the OWNER to check lines and grades.

21) PROPERTY BOUNDS

The CONTRACTOR shall exercise due care when working around all street and property bounds (whether granite, concrete, iron pins, wooden stakes, spikes or nails) that are to remain. Should any damage to a bound result from the actions of the CONTRACTOR, the bound shall be replaced and/or realigned by the CONTRACTOR with the assistance of a Professional Land Surveyor, as required by the OWNER, at no cost to the CITY. In the event of changes in grade and the bound is not to be replaced, the CITY will provide a frame and cover to be installed by the CONTRACTOR as incidental to the work with no additional cost to the CITY.

22) NOTICE TO UTILITY COMPANIES

The CONTRACTOR shall comply with MGL Chapter 82, §40. Written notice shall be given by the CONTRACTOR to all public service corporations or municipal and State officials owning or having charge of publicly or privately owned utilities at least one week in advance of commencement of operations that will affect such utilities. These shall include, but not be limited to gas, electricity, water and sewer, fire alarm, cable television or telephone services within the limits of the contract. The CONTRACTOR shall, at the same time, file a copy of such notice with the OWNER.

23) **SIGNS**

When signs are removed for purposes of construction they shall be replaced in a timely manner as required by the OWNER. Stop signs, Do Not Enter signs, one-way signs and any other signs that would leave hazardous conditions if removed shall be maintained unless appropriate safety precautions have been taken as approved by the OWNER.

24) PROTECTION OF UTILITY SERVICES AND MAINS

The CONTRACTOR shall make his own investigation and take due caution to assure that no damage to existing structures, mains, drainage lines, conduit, or other utilities will occur as a result of his operations. The CONTRACTOR shall notify Mass. DIG SAFE (888) 344-7233 and procure a DIG SAFE number at each location prior to disturbing ground in any way.

25) UTILITY COORDINATION

The CONTRACTOR shall be responsible for coordinating all efforts of the respective utility companies for any relocation or work efforts. Utilities include:

NSTAR	800 Boylston Street	Boston, MA 02199-8003	John Zappi	(339) 987-7768
National Grid	160 Newton Street	Waltham, MA 02452	Kevin Souza	(781) 398-7301
Verizon	480 Rear Arsenal Street	Watertown, MA 02472	Ed McCarthy	(617) 673-9060
Comcast	55 Concord Street	North Reading, MA 01864	Bob Hagwood	(508) 208-0646
RCN	201 University Ave	Westwood, MA 02090	Maintenance	(877) 726-7000
Street Dept.	167 Lexington Street	Waltham, MA 02452	Arthur Mullin	(781) 314-3859
Water & Sewer	169 Lexington Street	Waltham, MA 02452	Lisa Goyer	(781) 314-3828

26) ACCESS TO AREA MERCHANTS, BUSINESSES, HOUSES AND GARAGES

The CONTRACTOR shall adjust and provide a suitable vehicle and pedestrian access to all area merchants, businesses, houses and garages at all times as necessary and to the satisfaction of the ENGINEER.

27) MATERIALS

Slips for materials purchased to be used on the work shall be submitted to the OWNER prior to installation of the materials. All slips shall clearly show the type and/or class of the material and the quantity purchased. The Vendor's name shall be shown on all slips.

28) MATERIALS REMOVED AND STACKED

Unless otherwise specified, all materials to be removed and stacked shall remain the property of the City of Waltham. The CONTRACTOR shall carefully remove, transport and stack any of these materials at an area within the City of Waltham, designated by the OWNER. If the City does not want any of these materials, they shall become the property of the CONTRACTOR and shall be removed from the project site and properly disposed of at no additional cost to the CITY.

29) INVOICING

The contractor shall submit a separate invoice for each street and it shall include the total cost of improving said street/sidewalk including all equipment, labor, materials, police details, other safeguards as required and all else incidental thereto.

30) DISPOSAL OF SURPLUS MATERIAL

All existing and other materials not required or needed for use on the project, and not required to be removed and stacked, shall become the property of the CONTRACTOR and shall be immediately removed from the site during the construction period and legally disposed of.

31) PROTECTION OF CATCH BASINS AND WATER RESOURCES

The CONTRACTOR shall take great care to prevent excavated material and pavement from entering catch basins and manholes. In the event such material enters these structures, it shall be immediately removed. Silt fabric shall be installed between the grate and cover of catch basins and removed as soon as protection is no longer required.

32) DAMAGES

- (a) On any and all areas where work of any description whatsoever is performed, the CONTRACTOR shall be held strictly responsible for all damage in the execution of this contract and the restoration to the original condition of all driveways, walks, lawns, gardens, shrubbery, buildings, stone bounds, walls, ornamentals, utilities, etc., located within the locus of this contract and all to the satisfaction of the OWNER.
- (b) The CONTRACTOR further agrees that he will be responsible for any damage to any person or property resulting from defects or from any cause whatsoever during the progress of the work or at any time before its completion and final acceptance, and that he will indemnify and save harmless the CITY OF WALTHAM from all suits or actions of every name and description brought for or on account of injuries or damages received by any person or persons from the CONTRACTOR, his servants or agents, in the construction of said work or in consequence of any negligence regarding the same, or improper materials used in its construction, or by or on account or any act or omission of the CONTRACTOR or his agents.
- (c) The CONTRACTOR further agrees that so much of the money due to him under this contract or agreements, as shall be considered necessary by the MAYOR, may be retained by the CITY OF WALTHAM until such suits or claims for damages as aforesaid, shall have been settled and evidence to that effect furnished to the satisfaction of the MAYOR.

33) REPAIRS AND REPLACEMENTS

- (a) If at any time during the period of one year from the date of final completion of the work contemplated in this contract, as determined by the OWNER, any part of such shall, in the opinion of the OWNER require replacing or repairing, or damage to other property of the CITY is caused owing to any defect in the work, the OWNER may notify the CONTRACTOR in person or by mail to make the required repairs or replacements and repair such damage.
- (b) If the CONTRACTOR shall neglect to make such repairs or replacements to the satisfaction of the OWNER within ten days from the date of giving or mailing such notice, then the OWNER may employ other persons to make the same.
- (c) The CONTRACTOR agrees, upon demand, to pay the CITY all amounts that it expends for such repairs or replacements.

34) PUBLIC SAFETY AND CONVENIENCE

The CONTRACTOR shall provide necessary access for fire apparatus and other emergency vehicles through work zones to abutting properties at all times.

At the end of each working day, trenches shall be backfilled to grade, or covered with secured steel plates. Each edge of the plates shall either be beveled and lay flat, or protected by a bituminous ramp at a slope of two feet horizontally and one inch vertically. Any temporary patching material may be used to construct the ramps. The cost of patching materials, maintenance and removal will be considered incidental to items in the contract and there will be no separate payment.

Sweeping and cleaning shall be performed at the end of each day, and throughout the day when conditions warrant. Sweeping and cleaning shall be considered incidental to the work being performed. When requested by the OWNER, calcium chloride shall be applied to unpaved surfaces as specified under ITEM 440.000 of the Technical Provisions.


Sweeping and cleaning of surfaces beyond the limits of the project required to clean up material caused by spillage or vehicle tracking during the various phases of the work shall be considered as incidental to the work being performed under the Contract and there will be no additional compensation.

35) SAFETY SIGNAGE

Unless otherwise indicated, the CONTRACTOR shall provide safety signage, lighted drums and barricades for detours, road closings, parking restrictions, etc. at his expense. Sign materials, legends and mounts shall be approved by the OWNER prior to installation.

36) TRAFFIC POLICE

When, in the opinion of the OWNER, policemen are necessary for the directing of traffic, their services shall be paid for by the CONTRACTOR and the CONTRACTOR shall be reimbursed as specified under ITEM 999.001 of the Technical Provisions. To arrange for traffic police, telephone (781) 314-3604.



CLEARING AND GRUBBING

DESCRIPTION

General.

This work shall consist of clearing, grubbing, cutting, removal and disposal of all vegetation and debris from areas either within or outside of the Right-of-Way as shown on the plans or designated by the Engineer.

The work shall also include the preservation from injury or defacement of all vegetation and objects designated by the Engineer to remain.

The burning of trees, brush, stumps, etc., will not be permitted. The Contractor shall provide other satisfactory methods of disposal without additional compensation.

Quality of Work.

Quality of work must conform to all accepted tree trimming practices. All trimming and pruning shall conform to recognize tree surgery practices, and particular note should be made that painting with an approved tree dressing or paint, will be required on all cuts 2 inches or over in diameter.

The dressing or paint shall be applied no later than two days after the cuts are made.

Recognized tree surgery practices include among others, the fact that all limbs and branches which require removal and all stubs regardless of age must be cut flush either to a union with the next larger sound limb or branch or flush to the trunk of the tree.

The cutting shall be performed by experienced woodsmen. Trained tree climbers are required for pruning of tall growth. Care shall be exercised by the Contractor to prevent injury to trees and shrubs designed to be preserved. Any injury to limbs, bark or roots of such plants shall be repaired by the Contractor, as directed, or the plants replaced without additional compensation for such repair or replacement.

Disposal of Trees.

All trees to be cleared shall become the property of the Contractor, and the satisfactory disposal of the wood in such trees outside the Right-of Way shall become his responsibility.

The tress, including cuttings and slash shall be disposed after cutting as soon as practicable and in such a manner as not to distract from the appearance of the roadside.

If the existing ground in the area is disturbed by any of the work or equipment, the Contractor shall rough-grade and loam and seed if necessary the disturbed areas, if so directed, without additional compensation.

Payment Items

103.000	.03.000 Tree removed (diameter under 24 Inches)	
104.000	Tree removed (diameter Over 24 Inches)	Each

General

Disposal of Stumps and Brush.

After removal, all stumps including the major root system shall be disposed by the Contractor at his own responsibility outside the layout where the material will not cause obstructions to streams and will not detract from the appearance of the roadside.

Disposal of Dutch Elm Diseased Wood.

Dutch Elm diseased wood shall be disposed of in accordance with the provisions of General Law, Chapter 87, Section 5 and Chapter 132, Sections 8 and 11, as amended; and in accordance with any additional local regulations.

Where the work includes the removal of elm trees or the limbs of elm trees, such trees or limbs thereof shall be disposed of immediately after cutting or removal and in such a manner as to prevent the spread of Dutch elm disease. This shall be accomplished by covering them with earth to a depth of at least 6-inches in areas outside the highway location where the Contractor has arranged for disposal.

Where the work includes the removal and disposal of stumps of elm trees, such stumps shall be completely disposed of immediately after cutting in the manner specified above.

Method of Measurement.

Only such trees as have a shortest diameter of at least 9-inches and less than 24-inches shall be included in the item of Trees Removed (Diameter Under 24-Inches). Only such trees as have a shortest diameter of 24- inches or more shall be included in the item of Trees Removed (Diameter 24 Inches and Over).

The item of Stumps Removed shall include the removal and satisfactory disposal of all tree stumps which remain in their original position and 9 –inches or more in shortest diameter at the cutoff point, where the trees have been previously removed by others. A stump shall not be construed as a tree under these specifications unless the trunk extends over 6-feet above the average ground.

Trees or stumps to be removed which have the shortest diameter specified for payment will be measured in place by the following procedure.

Where the tree consists of a single trunk extending more than a 3-foot vertical height above the average natural ground line, the shortest diameter shall be measured at the 3-foot level above the average elevation of the original ground.

Any tree whose main trunk separates into multiple trunks or which has limbs or branches growing out from the main trunk below the 3-foot level defined hereinbefore shall have its shortest diameter measure at the lowest point on the main trunk where multiple growths or branching out begins.

Measurement for payment under the respective items shall be such that any individual growth to be classed as a tree stump shall be measured in a manner to limit payment to one single tree or stump at each particular location of the individual growth. When multiple trunks with a common root system are separated at ground level each separate trunk shall be considered as an individual growth under these specifications.

The quantity of trees or stumps to be paid for will be the number actually removed by the Contractor in the completed and accepted work as determine by count.

The removal of trees, including the stumps thereof and required spray material will be paid for at the contract unit price each for the particular kind of work involved, as defined hereinbefore when a quantity is given in the Proposal under their respective items, otherwise this work will be paid for at the contract unit price for excavation or at the contract unit price per acre of Clearing and Grubbing or Selected Clearing and Thinning, whichever is applicable. The contract unit price shall include the cost of all arrangements and methods required to protect from harm all existing overhead or underground installations. The contract unit price for the respective items shall not include any tees or stumps removed from the area paid for under the item of Clearing and Grubbing or Selected Clearing and Thinning.

Only such trees or stumps as have a shortest diameter of 9-inches and over, measured as stipulated in Sub-section 101.80 shall be included for payment.

Payment Items

105.000 Stump Removed Each

UNCLASSIFIED EXCAVATION

GENERAL: This work shall consist of the necessary excavation and removal of various materials as shown on the contract drawings or as required by the OWNER. All work shall be done by the CONTRACTOR. All excavated material shall be disposed of in a proper manner. All material shall be cleaned up by the CONTRACTOR as the work progresses. No material or waste shall be left on the street overnight and no driveways or sidewalks shall be left in a rough or unsafe condition unless lighted and guarded by the CONTRACTOR at his expense. Where abutting lawns are cut, the CONTRACTOR must properly adjust and reseed the lawn to the new grade. Where abutting surfaces of blacktop or other material are disturbed beyond the limit of adjustment, the CONTRACTOR shall replace same at his own expense.

Excavation shall include the removal and disposal of bituminous, earth, curbing, signposts, and/or any incidental items as indicated on the contract drawings or as required by the OWNER. Items and/or materials that are classified for payment under some other unit item within this contract shall not be considered as part of ITEM 120.100.

The edges of existing concrete surfaces that are to receive new replacement materials shall be saw-cut along even lines and shall be cut back to obtain clean, sound vertical edges of the abutting material.

The edges of bituminous concrete shall be saw-cut or cut with pneumatic tools along even lines and shall be cut back to obtain clean, sound vertical edges of the abutting material. All edges shall be coated with an approved bituminous material for proper bonding of new pavement construction with the existing pavements. All preparation of edges of existing pavements shall be provided as specified herein and shall be subject to approval by the OWNER.

The City of Waltham, at its own discretion, may retain the right to the excavated gravel and the OWNER may select a site for said gravel to be placed. On-site gravel, if requested by the OWNER, shall be saved for re-use on the job. The gravel shall be excavated separately from the bituminous, stored (if required) and/or relocated on the site or at a site within the city selected by the OWNER, at no additional cost to the City of Waltham. All work shall be done by the CONTRACTOR.

If requested by the OWNER, any suitable excess material (as determined by the OWNER) excavated from the site shall be re-used to fill areas below subgrade. This shall be done at no extra cost to the City.

All saw-cutting of materials shall be done at no extra cost and shall be considered as incidental to the item unless there is a separate and/or specific pay item listed for saw-cutting in the Contract.

CONTRACTOR shall avoid damage to trees that have parts of their root system in the roadway, sidewalk or planting areas that are selected for excavation. Said excavation shall be accomplished as carefully as possible or as required by the OWNER.

NOTE: Material excavated during reclamation or cold planing operations is not included in this item.

MEASUREMENT: Measurement for unclassified excavation shall be the number of cubic yards of material removed and legally disposed of. This quantity shall be based on the OWNER'S field measurements and/or office calculations.

Failure to allow ample time for the OWNER to make the required measurements will forfeit the CONTRACTOR'S right of claim to any excavation other than that allowed by the OWNER.

PAYMENT: Payment for unclassified excavation shall be made for the number of cubic yards of material removed and disposed of as determined above at the contract unit Bid price for ITEM 120.100 as set forth in the Bid. Unless it is classified for payment under some other unit item within this contract, sawcutting of pavements shall be considered as incidental to the work and shall be included within the unit price for unclassified excavation.

120.100	Unclassified Excavation	Cubic Yards
121.000	Class A Rock Excavation and Refill	Cubic Yards
123.200	Muck Excavation & Refill (trench)	Cubic Yards
127.000	Concrete Excavation	Square Yards

CONCRETE SIDEWALK EXCAVATION

GENERAL: This work shall consist of all necessary excavation and disposal of existing concrete surfaces as shown on the Contract Drawings or as specified by the OWNER. All work shall be done by the CONTRACTOR and the material shall be cleaned up as the work progresses. No material or waste shall be left on the street overnight and no driveway or sidewalk shall be left in an unsafe condition unless lighted and guarded by the CONTRACTOR at his expense. Where abutting surfaces of concrete or material are disturbed beyond the limits of adjustment or beyond the limits of contract, the CONTRACTOR shall replace the same at his own expense. If reinforced concrete walks and/or drives are encountered during removal, they shall be included as part of this item. The edges of existing concrete surfaces that are to receive new replacement materials shall be saw-cut along even lines and shall be cut back to obtain clean, sound vertical edges of the abutting material.

All saw-cutting of concrete shall be done at no extra cost and shall be considered as incidental to the work within this item unless there is a separate and/or specific pay item listed for saw-cutting elsewhere in this contract.

MEASUREMENT: Measurement shall be the number of square yards removed and disposed, regardless of the depth of concrete excavated, in a manner satisfactory to the OWNER. This quantity shall be measured in the field by the OWNER.

Failure to allow ample time for the OWNER to make the required measurements will forfeit the CONTRACTOR'S right-of-claim to any concrete excavation other than that allowed by the OWNER.

PAYMENT: Payment shall be made for the number of square yards of concrete removed, regardless of depth, based on the OWNER'S field measurements. Payment shall be at the Contract unit price for ITEM 127.000 as set forth in the Bid. Saw-cutting shall be considered as incidental to the work within this item. No separate payment shall be made for saw-cutting concrete unless otherwise specified elsewhere within this contract.

127.000	Concrete Sidewalk Excavation	Square Yards
120.100	Unclassified Excavation	Cubic Yards

COLD PLANNING

GENERAL: This work shall consist of the cold planing of bituminous concrete roadway surfaces to various depths up to 6 inches to produce a uniform surface for the application of a bituminous overlay as required by the OWNER. The CONTRACTOR shall cold plane the bituminous concrete surface to the depths, widths, grades and cross sections as indicated and/or as required by the OWNER. Material removed shall be disposed of legally and off the site.

METHOD: Catch basins shall be protected during the cold planing process by inserting silt fabric between each frame and grate. The fabric shall be removed immediately after all cuttings have been removed. Any cuttings that fall into the catch basin shall be removed by the CONTRACTOR.

The bituminous concrete surface shall be planed and profiled by a power operated planing machine or a grinder capable of removing, in one pass, a layer of bituminous concrete nine feet. The equipment shall be self-propelled with sufficient power traction and stability to maintain accurate depth of cut and slope and shall be equipped with all necessary safety devices such as flashing lights and back-up signals so as to operate in traffic with complete safety. The equipment will be capable of accurately and automatically establishing profile grades along each edge of the machine by referencing from the existing pavement or from an independent grade control and shall have an automatic system for controlling cross slope at a given rate.

All planing machinery shall be equipped with dust control devices to prevent any dust produced in the cutting operation from escaping into the air. Dust control equipment must comply with EPA air quality standards.

The CONTRACTOR shall also have the necessary auxiliary grinding or milling machinery to perform the required cutting and trim cutting around castings. Pneumatic rubber-tire mounted equipment shall be used only for trimming and edging operations.

The cold plane cuttings from the operation shall be discharged directly from the planer into the CONTRACTOR'S trucks and legally disposed of off the site by the CONTRACTOR in a manner acceptable to the OWNER. Unless otherwise specified by the OWNER, the materials shall become the property of the CONTRACTOR. Loose materials left on the roadway surface as a result of the cold planing operations shall be removed and disposed of by the CONTRACTOR in the same manner as the planed material.

All excess material shall be removed from the site as part of this item. **There is no additional measurement or payment for excavation.**

MEASUREMENT: Measurement for cold planing shall be for the number of square yards of material removed and disposed of, regardless of depth, as accepted and measured by the OWNER.

PAYMENT: Payment for cold planing shall be made for the number of square yards of materials cold planed and removed and properly disposed of, regardless of depth, as determined above at the contract unit price for ITEM 129.010 as set forth in the Bid. Said price and payment shall be full compensation for furnishing all equipment, labor, materials, tools, and all else incidental and necessary for the satisfactory completion of this work.

Payment Item

129.010 Cold Planing Square Yards

GRAVEL BORROW

GENERAL: This work shall consist of furnishing and placing ordinary gravel borrow in accordance with these Specifications, and/or as required by the OWNER.

MATERIALS: Gravel borrow shall consist of hard durable stone and coarse sand free from loam and clay, well graded and containing no stone having any dimension greater than two (2) inches (type C), as per Section M1.03.0 of the Commonwealth of Massachusetts Standard Specifications, including any and all addenda. The gravel borrow shall conform to the following sieve requirements:

<u>SIEVE</u>	<u>% PASSING</u>
1/2"	50 - 85
#4	40 - 75
#50	08 - 28
#200	0 - 08

The gravel shall be tested for sieve analysis at the plant prior to delivery on the job site. The written results shall be given to the inspector for the city for approval prior to delivery. Failure to do so may result in the refusal of the material by the City. All costs incurred shall be paid for by the CONTRACTOR at no cost to the City.

The gravel borrow shall be placed in six inch (maximum) layers and then compacted to not less than 95% of maximum optimum density as determined by AASHO Test Designation: T99-57, Method C.

Crusher run may be substituted in place of gravel borrow if desired by the CONTRACTOR and so approved by the OWNER. Crusher run shall be paid for at the same unit price as gravel borrow. The conversion factor used in determining the quantity of crusher run substituted shall be one and one-half tons of crusher run is equivalent to one cubic yard of crusher run.

MEASUREMENT: Measurement for gravel borrow shall be the number of cubic yards furnished, placed, and accepted in accordance with these specifications and/or as required by the OWNER. The number of cubic yards in place and accepted shall be measured or calculated by the OWNER. Fifteen percent shall be added to the figure for compaction. Only gravel borrow placed within the established pay limit necessary to complete the work as required by the OWNER shall be considered for payment. If, in the opinion of the OWNER, the CONTRACTOR has excavated areas to an excessive width and/or depth, either through error or for his own convenience, the gravel borrow used to refill trenches beyond said reasonable width or depth shall be paid for by the CONTRACTOR with no cost to the City.

Failure to allow the OWNER ample time to make the required measurements will forfeit the CONTRACTOR'S right of claim to any gravel borrow other than that which is allowed by the OWNER.

PAYMENT: Payment for gravel borrow shall be made for the number of cubic yards furnished, placed, and accepted as determined above at the contract unit prices for ITEMS 151.000 & 151.220 as set forth in the Bid. Said price and payment shall be full compensation for furnishing and placing all materials, all equipment, tools, labor, backfilling operations and all else incidental thereto. Fine grading and compaction shall be paid for under the applicable item of finish material (bituminous concrete or cement concrete).

On-site gravel, if requested by the OWNER, shall be saved for re-use on the job. The gravel shall be excavated, stored (if required), and/or relocated on the site, all at no additional cost to the City. All work shall be done by the CONTRACTOR.

Payment Items

151.220 Gravel Borrow (Trench Repair, Sidewalks & Drives) Cubic Yards

CRUSHER RUN

GENERAL: This work shall consist of the furnishing and placing of a one-inch leveling layer of crusher run as required by the OWNER. Depth of crusher run shall be measured after compaction. Crusher run may also be provided as a base for granite curb if required by the OWNER.

MEASUREMENT: All crusher run used will be paid for on the basis of weight and shall be measured by tickets delivered with each load. The tickets shall clearly show the total, tare, and net weights. Loads represented by tickets not showing the weights as specified above will not be accepted for payment. Only crusher run placed at the required depth and within the limits specified will be accepted for payment.

PAYMENT: Payment for crusher run shall be made for the number of tons as determined above at the contract unit price for ITEM 151.900 as set forth in the Bid. Said price and payment shall be full compensation for furnishing and placing of crusher run, and for furnishing all tools, labor, equipment and all else incidental thereto. Fine grading and compaction of crusher run shall be paid for under the applicable item of finish material (bituminous or cement concrete).

Payment Item

151.900 Crusher Run Tons

SAND BORROW

GENERAL: This work shall consist of furnishing and mixing sand borrow as an additive for reclamation applications.

MEASUREMENT: Sand borrow will be paid for on the basis of weight and shall be measured by tickets delivered with each load. The tickets shall clearly show the total, tare, and net weights. Loads represented by tickets not showing the weights as specified above will not be accepted for payment.

PAYMENT: Payment for sand shall be made for the number of tons as determined above at the contract unit price for ITEM 154.001 as set forth in the Bid. Said price and payment shall be full compensation for furnishing and placing of sand, and for furnishing all tools, labor, equipment and all else incidental thereto.

Payment Item

154.001 Sand Borrow Tons

DRAINAGE STRUCTURE ADJUSTED

GENERAL: This work shall consist of adjusting OWNER'S existing frames and grates or covers of manholes and catch basins to newly proposed line and/or grade changes. **This item shall not apply to any new castings installed under item 222.010 or castings for new structures**. When the line and/or grade of an existing structure require a change of more than one foot vertically and/or horizontally, the structure shall be remodeled under ITEM 220.500.

METHOD: Frames shall be set in full mortar beds true to the lines and grades established by the OWNER. All voids beneath the bottom flange shall be entirely filled to make a water-tight fit. A ring of mortar at least one inch thick shall be placed around the outside of the bottom flange and shall extend to the outer edge of the masonry structure.

After frames have been set and mortared, a cement concrete collar shall be constructed to the dimensions shown on the detail plans of the contract drawings. Cement concrete shall be 3000 psi with ¾ inch stone. All work shall be done under the direction of the OWNER.

PAYMENT: Measurement for drainage structures adjusted shall be made based on a complete and accepted unit as determined from actual count by the OWNER.

Payment shall be made for each completed unit as determined above at the contract unit price for ITEM 220.000 as set forth in the Bid. Said price and payment shall be full compensation for all work including labor, materials, tools, equipment, mortar, brick, gravel, collars and all else necessary for final and satisfactory completion of the work within this item.

220.000	Drainage Structure Adjusted	Each
220.500	Drainage Structure Remodeled	Vertical Foot
222.010	Frame and Grate or Cover	Each

DRAINAGE STRUCTURE REMODELED

GENERAL: This work shall consist of remodeling existing drainage structures, as required, to conform to newly proposed line and/or grade changes. The work shall be in accordance with these specifications or as required by the OWNER. **This item shall not apply to new castings for new structures**

When the line and/or grade of an existing drainage structure require a change of more than one foot vertically and/or horizontally, the structure shall be remodeled unless otherwise specified by the OWNER.

METHOD: Closing blocks and/or bricks shall be removed to expose the barrel portion of the structure. The barrel portion shall then be altered according to the new line and/or grade. Closing blocks and/or bricks shall then be reset to the structure. All masonry work shall be completed to the satisfaction of the OWNER. The CONTRACTOR shall be held responsible for the protection of the castings and the materials during construction operations. Any materials or castings damaged by the CONTRACTOR shall be replaced at his own expense and at no cost to the City.

Frames shall be set in full mortar beds true to the lines and grades established by the OWNER. All voids beneath the bottom flange shall be entirely filled to make a water-tight fit. A ring of mortar at least one inch thick shall be placed around the outside of the bottom flange and shall extend to the outer edge of the masonry structure.

MEASUREMENT: Measurement for drainage structures remodeled shall be made for the number of vertical feet the structure has been altered. Limits of measurement shall be from the top of the undisturbed row of blocks or barrel portion up to one foot below proposed finished rim grade of the casting. Final adjustment of the casting to finished grade shall be done under ITEM 220.000 or item 222.010 and shall not be considered for measurement or payment under this item. Measurement shall be made in the field by the OWNER.

PAYMENT: Payment for drainage structures remodeled shall be made as determined above at the contract unit price for ITEM 220.500 as set forth in the Bid. Said price and payment shall be full compensation for all materials required, all tools, labor, equipment, excavation, backfill & backfilling operations and all else incidental to complete the work within this item. All work is subject to final approval by the OWNER.

220.500	Drainage Structure Remodeled	Vertical Foot
220.000	Drainage Structure Adjusted	Each
222.010	Frame and Grate or Cover	Each

FRAME & GRATE OR COVER (IN-PLACE) (MUNICIPAL STANDARD or MHD CASCADE TYPE)

GENERAL: This work shall consist of furnishing, setting and adjusting to final grade any new castings as required.

When existing castings, in the opinion of the OWNER, are found to be defective through no fault of the CONTRACTOR, they shall be removed and disposed of by the CONTRACTOR. A new complete casting shall then be furnished, installed and adjusted to final grade by the CONTRACTOR as required by the OWNER.

Any casting damaged by the CONTRACTOR through his own negligence shall be replaced by him at no additional cost to the City.

MATERIALS: For catch basins, the frames shall conform to LeBaron type LF 246 (3 flange when curbing is present, 4 flange if there is no curbing) or the equivalent. Grates shall conform to LeBaron type L24-SG8 for standard grates or LK121A for cascade type grates or the equivalent.

For manholes, the frames shall conform to LeBaron type LA 246 or the equivalent. Covers shall conform to LeBaron type L24C19 or the equivalent. When ordering the covers, specify whether the top is to be lettered as "SEWER" or "DRAIN".

METHOD: Frames shall be set in full mortar beds true to the lines and grades established by the OWNER. All voids beneath the bottom flange shall be entirely filled to make a water-tight fit. A ring of mortar at least one inch thick shall be placed around the outside of the bottom flange and shall extend to the outer edge of the masonry structure.

MEASUREMENT AND PAYMENT: Measurement for frames and grates or covers shall be made for the number of units furnished, placed, adjusted to final grade and accepted as determined from actual count by the OWNER. Payment shall be made based on the number of completed units as determined above at the contract unit price for ITEMS 222.010 & 222.030 as set forth in the Bid. Said price and payment shall be full compensation for furnishing, setting and adjusting all castings, for materials including mortar, bituminous, red clay bricks, gravel, and for all tools, labor, equipment and all else incidental to the work within this item. There shall be no payment under this item for existing castings or for new or proposed castings that are being paid for as part of some other item within this contract.

222.010	Frame and Grate or Cover	Each
	(In-Place)(Municipal Standard)	
222.030	Frame and Grate or Cover	Each
	(In-Place)(MHD Cascade Type)	

GATE BOXES

GENERAL: This work shall consist of furnishing and installing gate boxes as shown on the contract drawings or as required by the OWNER.

Gate boxes shall be two section, cast iron, heavy pattern, adjustable type with cast iron cover. The upper section shall have a bottom flange of sufficient bearing area to prevent settling. The bottom section shall enclose the valve stuffing box and operating nut. Boxes shall be of lengths adapted to five foot pipe cover or more and have a minimum of six inch overlap in the most extended position. Covers shall have the word "WATER" cast in the top.

The box shall be installed vertically and centered over the gate so that the gate wrench may be easily attached onto the gate. After installation, the box shall be cleaned out of all residue. Also included with this item shall be the final adjustment to proposed grade of the new gate box.

MEASUREMENT: Measurement for gate boxes shall be for the number of units furnished, installed and accepted as measured by the OWNER.

PAYMENT: Payment for gate boxes shall be made for the number of units furnished, installed and accepted as determined above at the contract unit prices for ITEMS 357.040, 357.041, 357.060 and 357.061 as set forth in the Bid. Said price and payment shall be full compensation for furnishing and installing gate boxes and all related work including excavation, pumping, backfill, cement concrete collars, cleaning out the gate box, all tools, labor, equipment, materials and all else incidental to complete the work within this item. There shall be no separate payment for adjustment of new gate boxes and sleeves. That work shall be considered as incidental to the work within this item.

	Payment Items	
357.040	4" Service Gate Box	Each
357.041	4" Service Gate Box (Upper Sleeve Only)	Each
357.060	6" Service Gate Box	Each
357.061	6" Service Gate Box (Upper Sleeve Only)	Each

ADJUSTMENT OF GATE BOXES

GENERAL: This work shall consist of raising the OWNER'S existing water gate and water service gate boxes to newly proposed grades. Prior to adjustment of the gate boxes, the vertical alignment of the box over the center of the gate shall be checked. If needed, the gate box shall be re-aligned over the top of the gate before it is adjusted. Gravel base around the gate boxes shall be thoroughly compacted. For gate boxes in the traveled roadway, the excavated area shall be refilled with gravel, compacted, and set in a cement concrete collar as shown on the detail section of the contract drawings. The final elevations of the structures shall be determined in the field by the OWNER at the time of construction. All work shall be done under the direction of the OWNER. After the boxes are adjusted, they shall be air blown to remove all debris form the inside.

If, during the course of the work, a defective gate box is encountered, the CONTRACTOR shall remove it as required by the OWNER. A new gate box and/or sleeve shall be furnished and installed by the CONTRACTOR. This shall not include any gate boxes and/or sleeves damaged by the CONTRACTOR. Any damage as a result of the CONTRACTOR'S negligence shall be repaired or replaced by him at no cost to the City. Furnishing, installation and adjustment to final grade of any new gate boxes and/or sleeves shall be included as part of ITEMS 357 and shall not be considered as part of ITEMS 358.100 or 358.200.

MEASUREMENT: Measurement for gate boxes adjusted shall be for the number of units completed and accepted as determined from actual count by the OWNER.

PAYMENT: Payment for gate boxes adjusted shall be made based on the number of completed units as determined above at the contract unit prices for ITEMS 358.100 & 358.200 as set forth in the Bid. Said price and payment shall be full compensation for all work in adjusting gate boxes and/or sleeves including all tools, labor, equipment, cement concrete collars, gravel, compaction, and all else incidental to satisfactorily complete the work within this item. Not included for payment within this item shall be the furnishing, installation, and final adjustment to grade of any new gate boxes and/or sleeves that are required. They shall be measured and paid for under ITEMS 357.

358.100	Adjustment of Gate Boxes (Sidewalk)	Each
358.200	Adjustment of Gate Boxes (Roadway)	Each

PAVEMENT RECLAMATION

GENERAL: This work will consist of in-place rehabilitation of the existing pavement structure. Existing pavement shall be scarified, pulverized and reshaped into a processed asphalt stabilized base.

MATERIALS: If additional fine material is required to attain the specified gradation, it will be added as required by the OWNER and paid under item 154.001.

METHODS: The existing asphalt structure shall be scarified and mixed with equal amounts of gravel base from the existing roadway foundation to a maximum depth of 16". The pulverization shall be accomplished by means of a traveling pulvimiller/hammermill or equivalent machine capable of scarifying/milling to a depth of 16" in one pass and conveying this material to a stationary hammermill mounted on the machine. This machine shall be self-propelled and equipped with an adjustable grading blade thus leaving its path generally smooth for traffic. The key element in this process is the fractioning of the existing asphalt pavement by the high speed hammers of the hammermill. Equipment such as road planers/cold milling machinery will not be acceptable as they produce larger asphalt particle size that defeats the objective of this process. The above mentioned process shall produce a uniformly blended base material with a minimum asphalt content of 2% that will conform to the following gradation requirements:

Sieve Designation	Percentage by Weight Passing
3"	100%
1 1/2"	70-100%
3/4"	55-90%
#40	10-30%
#200	1-3%

After the material has been accepted by the OWNER, it shall be shaped, graded and rolled to true grades, the prescribed number of inches below and parallel to the finish pavement grade of the roadway as shown on the plans or as required by the OWNER. Material not required in the roadway shall be deposited and spread on the sidewalk by the CONTRACTOR as required at no additional cost to the City. Excess material that is not needed on this project shall be removed and properly disposed of by the CONTRACTOR at no additional cost to the City.

Water shall be applied during the operation in sufficient quantities to insure optimum moisture content at the time of compaction. Water may be taken from City hydrants provided an approved hydrant wrench and control valve are used, and that water is not wasted.

MEASUREMENT: Measurements shall be taken by the OWNER with the process material in place and properly graded and compacted. Measurement shall be the number of square yards reclaimed for any depth up to sixteen inches.

All excess material shall be removed from the site as part of this item. **There is no additional measurement or payment for excavation.**

PAYMENT: Payment shall be made for the number of square yards reclaimed as determined above, up to a depth of sixteen inches, at the contract unit price for ITEM 403.001 as set forth in the Bid. Said price and payment shall be full compensation for reclaiming, processing, rough grading, compacting, depositing and grading on sidewalk, **removal of excess material**, labor, materials, tools and equipment and all incidentals necessary to complete the work under this item as shown on the plans, as required by the OWNER, and as specified herein.

403.001	Reclamation	Square Yards
154.001	Sand	Tons

TRENCH REPAIR

GENERAL: This work shall consist of repairing temporary trench patches throughout the city which were previously installed by others. Work shall include saw cutting and excavation of the temporary patch, compacting the sub grade, applying a 1½" binder course and returning on the following day to apply a 1½" wearing course. Trenches are generally 100 to 400 square feet and a located throughout the city.

MATERIALS: Class I bituminous concrete pavement, Type I-1, shall conform to the requirements of Section 560.00 of the current Edition of the "Standard Specifications for Highways and Bridges," Commonwealth of Massachusetts, Department of Public Works, including any addenda or amendments thereto.

Bituminous concrete shall be spread at a temperature of not less than 225 degrees Fahrenheit and all initial rolling or tamping shall be performed when the temperature of the mixture is such that the sum of the air temperature plus the temperature of the mixture is between 300 and 375 degrees Fahrenheit. All mixtures shall be placed only when the atmospheric temperature is above 40 degrees Fahrenheit.

Bituminous concrete for wearing surfaces and base courses shall be spread in individual layers and compacted to the required lines, grades and cross section. Each completed surface shall be thoroughly compacted, smooth and free from ruts, humps, depressions, or irregularities. Where new bituminous meets existing bituminous surfaces, an emulsifying agent shall be applied to seal the joint. A sand overcoat shall then be applied over the emulsifying agent.

MEASUREMENT: All bituminous used for trench repair shall be paid for on the basis of square yards as measured by the OWNER. Only bituminous concrete placed at the required depth and within the limits specified by the OWNER will be accepted for payment.

PAYMENT: Payment for Trench Repair shall be made for the number of square yards as determined above at the Contract unit price for ITEM 405.000 as set forth in the Bid. Said price and payment shall be full compensation for all saw cutting, excavation and disposal, fine grading and compaction, spreading and compacting bituminous concrete, emulsifying and sanding of all joints, and for furnishing all tools, labor, **materials**, equipment, and all else incidental thereto.

Payment Item

405.000 Trench Repair Square Yard

CALCIUM CHLORIDE FOR DUST CONTROL

GENERAL: This work shall consist of furnishing and applying approved dust control material to the surface of the sub grade or elsewhere as required by the OWNER.

MATERIALS: Calcium Chloride shall conform to the requirements of AASHO M144, Type I or Type II.

APPLICATION: Calcium Chloride shall be uniformly applied at the rate of three-quarters pounds per square yard or as required by the OWNER.

MEASUREMENT: Calcium Chloride will be measured by the pound and the quantity to be paid for shall be the actual weight of the material furnished and applied in place.

PAYMENT: Payment shall be made for the amount of Calcium Chloride furnished and placed as determined above at the Contract price for ITEM 440.000 as set forth in the Bid.

Payment Item

440.000 Calcium Chloride Pounds

GENERAL: This work shall consist of fine grading and compaction of gravel base material and/or crusher run base material prior to placing mix, and furnishing, spreading and compacting bituminous concrete base courses and wearing surfaces in accordance with the details shown on the Contract Drawings, as specified in these Specifications, or as required by the OWNER.

MATERIALS: Class I bituminous concrete pavement, Type I-1, shall conform to the requirements of Section 560.00 of the current Edition of the "Standard Specifications for Highways and Bridges," Commonwealth of Massachusetts, Department of Public Works, including any addenda or amendments thereto. The City of Waltham has the option of requesting a modified state top when deemed necessary.

Bituminous concrete shall be spread at a temperature of not less than 225 degrees Fahrenheit and all initial rolling or tamping shall be performed when the temperature of the mixture is such that the sum of the air temperature plus the temperature of the mixture is between 300 and 375 degrees Fahrenheit. All mixtures shall be placed only when the atmospheric temperature is above 40 degrees Fahrenheit.

Bituminous concrete for wearing surfaces and base courses shall be spread in individual layers and compacted to the required lines, grades and cross section.

Rolling shall commence at the lower edges and shall progress toward the highest portion. Under no circumstances shall the center be rolled first. Each completed surface shall be thoroughly compacted, smooth and free from ruts, humps, depressions, or irregularities.

Where new bituminous meets existing bituminous surfaces, an emulsifying agent shall be applied to seal the joint. A sand overcoat shall then be applied over the emulsifying agent.

MEASUREMENT: All bituminous used for roadway and sidewalk bases and surfaces will be paid for on the basis of weight and shall be measured by tickets delivered with each load. The tickets shall be signed by a certified weigher and shall be countersigned by the OWNER. The tickets shall clearly show the total, tare, and net weights. Loads represented by tickets not showing the weights as specified above will not be accepted for payment. Only bituminous concrete placed at the required depth and within the limits specified by the OWNER will be accepted for payment.

PAYMENT: Payment for bituminous concrete shall be made for the number of tons as determined above at the Contract unit price for ITEMS 460.000, 460.100 and 460.300 as set forth in the Bid. Said price and payment shall be full compensation for all fine grading and compaction, for furnishing, spreading and

compacting bituminous concrete, emulsifying and sanding of all joints, and for furnishing all tools, labor, materials, equipment, and all else incidental thereto.

460.000	Class I Bituminous Concrete Type I-1 (Roadway)	Tons
460.100	Class I Bituminous Concrete Type I-1 (Sidewalks, Drives, Permanent Patching & Adjustment. Areas)	Tons
460.300	Class I Bituminous Concrete Type I-1 (Roadway) Night Work	Tons

BITUMEN FOR TACK COAT

GENERAL: This work shall consist of furnishing and placing of a bituminous tack coat prior to the placement of Class I bituminous concrete for resurfacing. All work and materials shall be furnished and placed by the CONTRACTOR.

MATERIALS AND METHODS: Bituminous tack material shall conform to the requirements of Section M3.03.0 of the current Edition of the "Standard Specifications for Highways and Bridges," Commonwealth of Massachusetts.

The application shall be done by means of an approved mechanical pressure distributor tanker truck only with a heating device capable of heating the material evenly up to a temperature of 425° Fahrenheit. It shall also be equipped with a distribution spray bar of a type that will distribute the bituminous tack material uniformly under a pressure of not less than 30 lbs. per square inch, without streaks and/or spots, so as to provide an equal and uniform coverage on the existing surface. The tanker truck shall be equipped with a gauge to accurately measure the gallons applied. The tanker truck shall also be so designed as to enable the operator to control the rate of flow and to provide a positive cut-off to prevent dripping of the nozzles when shut off. The bitumen shall be applied at a rate as described above.

The application rate for the bitumen shall be 15 square yards per gallon.

MEASUREMENT: Measurement for bitumen for tack coat shall be for the number of gallons actually furnished, placed and accepted as determined by the OWNER and/or his representative. The OWNER and/or his representative may elect to use the measured amount from printout slips of actual gallons used as received from the tanker truck.

PAYMENT: Payment for bitumen for tack coat shall be made for the number of gallons furnished, placed and accepted as determined above at the Contract unit price for ITEMS 464.000 as set forth in the Bid. Said price and payment shall be full compensation for furnishing and placing all materials and for furnishing all tools, equipment, labor, and all else incidental thereto to complete the work within this item.

Payment Item

464.000 Bitumen for Tack Coat Gallons

BITUMINOUS CONCRETE CURB

GENERAL: This work shall consist of furnishing and placing bituminous concrete curb in accordance with these specifications or as required by the OWNER.

MATERIALS: Bituminous concrete curb, Class I, Type 2, shall conform to Commonwealth of Massachusetts SD106.2.0.

METHODS: On newly constructed roadways, the bituminous concrete curb shall be placed on a bituminous concrete roadway binder course. On existing roadways, the bituminous concrete curb shall be placed on a bituminous concrete pad of top course mix one foot wide by three inches deep at the gutter line in the existing roadway. The bituminous concrete curb shall be placed and compacted by machine. If, at anytime before the acceptance of the work, any soft or imperfect spots develop in the exposed surface of the curb, such material placed shall be removed and replaced with new material and compacted, at no additional cost to the OWNER.

PAYMENT: Payment shall be made for the number of linear feet of bituminous curb placed and accepted by the OWNER as determined above at the Contract unit price for ITEM 470.000 as set forth in the Bid. Said price and payment shall be full compensation for all materials, including bituminous concrete curb mix, all labor, tools, equipment, and related work and all else incidental thereto with the exception of the pad for the curb. The bituminous concrete binder course or the bituminous concrete shall be measured and paid for as part of ITEM 460.000 (binder course) or ITEM 460.100 (bituminous pad), whichever item applies.

470.000	Bituminous Concrete Curb (Class I - Type 2)	Linear Feet
460.000	Class I Bituminous Concrete Type I-1 (Roadway)	Tons
460.100	Class I Bituminous Concrete Type I-1 (Sidewalks, Drives, Permanent Patching & Adjustment Areas)	Tons

GENERAL: Under these items, the CONTRACTOR is to furnish and install new granite curbing, inlet stones, granite edging and curb corners. Curb shall be set on undisturbed earth to the lines and grades indicated on the Contract drawings and/or as required by the OWNER.

MATERIALS: All new granite curb, curb corners, and inlet stones and granite edging shall conform to the applicable requirements of the "Standard Specification for Highways and Bridges," Commonwealth of Massachusetts, including any addenda or amendments thereto with the exception of payment for crusher run. Crusher run for curbing shall be included as part of the applicable curb item. All granite curbing shall consist of at least ninety percent of six feet minimum lengths unless otherwise required by the OWNER.

Granite curb shall be hard, durable, fine to medium grain and free from seams that impair structural integrity. Color shall be light gray, highlighted by black flakes, similar to that installed on recent projects in Waltham. Curb for each location shall be fabricated from the same parent material by one manufacturer to give a uniform appearance. Natural variations characteristic of the deposit will be permitted. The top of the curb shall be polished. The sides shall be cut square, most specifically the top 6" of the face that faces the street.

Cement concrete shall be 2,500 psi, 3/4" stone.

METHOD: Granite edging shall be set in accordance with the "Commonwealth of Massachusetts Standard Specifications for Highways and Bridges."

A trench shall be excavated to a width of eighteen inches to the bottom of the proposed curb. Unless otherwise required by the OWNER, curb shall be set to the lines and grades shown on the plans and fitted together as closely as possible. Curb shall be saw cut, not broken, to required lengths. If requested by the OWNER, crusher run shall be added and hand tamped to fill any voids between the undisturbed earth and the bottom of the curb so the curb is supported along two points of its entire length. The center and both ends of each curb length shall be left open for cement concrete. On the day of the curb installation, 6" x 6" beds of cement concrete shall be poured front and back, and the concrete shall flow under the curb. Care shall be taken not to affect the line and/or grade of the curb. Joints between curbstones shall be filled with mortar and exposed surfaces shall be neatly pointed. At completion of work, curb shall be clean and free of cement spills. If curb is not clean, the OWNER may request that the curb be pressure washed, at no additional cost to the City.

Care should be taken to avoid placing concrete in areas selected for future placement of trees.

MEASUREMENT: Granite curb to be paid for will be the length actually furnished, set, completed and accepted in accordance with the Specifications and Contract Drawings and as measured along the outer radius of the curb. The quantity of new granite curb corners and inlet stones shall be on a unit basis for the actual number furnished and set in accordance with the Specifications and Contract Drawings.

PAYMENT: Payment for granite curb shall be made as determined above at the Contract unit prices for ITEMS 504.— as set forth in the Bid. Said price and payment shall be full compensation for furnishing and

setting new Type VA4 granite curb, furnishing and setting new Type A curb corners, furnishing and setting new inlet stones, all excavation, backfilling, cement concrete, and for furnishing all labor, tools, equipment, etc., and all else incidental to the satisfactory completion of the work included within these items.

504.000	Granite Curb Type VA4 Straight	Linear Foot
504.100	Granite Curb Type VA4 Curved	Linear Foot
504.110	Granite Curb Type VA4 Curved	Linear Foot
	(Less than 10' radius)	
506.000	Granite Curb Type VB (5"x18")	Linear Feet
506.100	Granite Curb Type VB (5"x18") Curved	Linear Feet
514.000	Granite Inlet Stone Straight	Each
516.000	Granite Curb Corner-Type A (2'-0"radius)	Each
517.000	Granite Curb Corner-Type B (3'-0"radius)	Each
121.000	Class A Rock Excavation	Cubic Yard
151.900	Crusher Run	Tons

CURB REMOVED AND RESET

GENERAL: This work shall consist of removing existing curb and/or curb corners and resetting them to grade in the same location in accordance with these specifications, as shown on the Contract Drawings, and/or as required by the OWNER. The CONTRACTOR assumes full responsibility for any damages incurred in the removal and resetting processes or any damages incurred while executing said work.

METHODS: Unless otherwise required by the OWNER, curb shall be set to the lines and grades shown on the plans and fitted together as closely as possible. Crusher run shall be added and hand tamped to fill any voids between the undisturbed earth and the bottom of the curb so the curb is supported along two points of its entire length. The center and both ends of each curb length shall be left open for cement concrete. On the day of the curb installation, 6" x 6" beds of cement concrete shall be poured front and back, and the concrete shall flow under the curb. Care shall be taken not to affect the line and/or grade of the curb. Joints between curbstones shall be filled with mortar and exposed surfaces shall be neatly pointed.

MEASUREMENT: Payment for granite curb removed and reset shall be the number of linear feet of curb actually removed and reset as measured and accepted by the OWNER. The quantity of curved granite curb and granite curb corners removed and reset shall be measured along the outer radius.

PAYMENT: Payment for curb and/or curb corners removed and reset shall be made for the number of linear feet of curb and/or curb corners actually removed and reset as determined above at the Contract unit prices for ITEM 580.000 as set forth in the Bid. Said price and payment shall be full compensation for furnishing all labor, tools, equipment, excavation, gravel borrow, backfill, and all else incidental thereto.

Payment Item

580.000 Curb Removed and Reset Linear Foot

GENERAL: This work shall consist of fine grading and compaction of gravel and/or crusher run and the furnishing and placing of cement concrete for sidewalks, driveways and aprons in accordance with these Specifications and/or as required by the OWNER. Depths of concrete shall be 4 inches (reinforced) in sidewalks and 6 inches (reinforced) in driveways, aprons and roundings and as required by the OWNER.

MATERIALS: 7% ($\pm 1\%$ %) air-entrained cement concrete (4,000 psi, 3/4" stone), borrow, and pre-formed joint fillers shall conform to the requirements of SECTION 701 of the "Standard Specifications for Highways and Bridges," Commonwealth of Massachusetts, Department of Public Works, 1988 Edition, including any addenda or amendments thereto, unless otherwise specified by the OWNER.

All concrete shall contain a fibrous concrete reinforcement of 100% virgin polypropylene fibrillated fibers of multi-design gradation as manufactured by Fibermesh, Synthetic Industries, 4019 Industry Drive, Chattanooga, Tennessee 37416 or an approved equal.

Wheelchair ramps shall include a prefabricated truncated dome modular system manufactured from high strength polymer concrete. Each accessible ramp shall have one panel 24 inches deep by 60 inches wide. The color of the panels shall be gray. The physical properties of the concrete panels shall meet the following requirements.

PROPERTY	VALUE
Water Absorption – ASTM D570	≤ 0.35%
Slip Resistance – ASTM C1028	≥ 0.80
Abrasive Wear – ASTM D2486	BYK Gardner Tester
	≤ 0.03/1,000 cycles
Accelerated Weathering – ASTM G26	≥ 2,000 hours no
	fading
Chemical Stain Resistance – ASTM	no discoloration
D543	
Gardener Impact – ASTM D5420	≥ 450 in. lbf/in.
Compressive Strength – ASTM D695	≥ 18,000 psi

Tactile warning panels shall be installed in accordance with the manufacturer's recommendations and tamped into the fresh concrete and made flush with the surrounding surfaces. Concrete masonry blocks may be needed to insure continuous contact with the panel's underside with the concrete. Panels shall be protected from damage and concrete and asphalt spatter. Surfaces shall be cleaned as recommended by the manufacturer.

The concrete of the surrounding ramp shall be finished true and smooth to the required dimensions and slope before the tactile warning panel is installed. The panel shall be placed true and square to the curb line.

METHODS: Methods shall conform to the aforesaid, unless otherwise required by the OWNER. All transverse joints shall be formed with a 1/2" wide by 1" deep jointing tool such as the Marshall Town No. 836 jointing tool or the equivalent. All transverse joints shall be measured and divided equally and

separately between the expansion joint distances. Continuous concrete blocks shall be no longer than 30 feet.

Concrete shall have a broom finish. A colored curing agent or retardant approved by the OWNER shall be applied to the finished concrete if requested by the OWNER. Otherwise, the curing method shall be as prescribed in Section 476.71A of the Mass. Standard Specifications.

The CONTRACTOR shall be responsible for the guarding of the wet concrete until it has sufficiently set up in place. The CONTRACTOR shall assume responsibility for replacing any concrete that is damaged due to cracking or vandalism. Replacement of concrete including saw cutting, removal and disposal of rejected concrete shall be done at the CONTRACTOR'S expense with no additional cost to the City. The CONTRACTOR maintains responsibility for the concrete for one year after the completion of the entire contract as noted in the Specifications of these documents (Section 6 Paragraph 8)

MEASUREMENT: Measurement for concrete sidewalks, drives and aprons shall be the number of square yards furnished, placed and accepted based on the OWNER'S field measurements or office calculations. Only cement concrete placed at the required depths and within the limits specified by the OWNER shall be accepted for payment.

PAYMENT: Payment for cement concrete sidewalks, drives and aprons shall be made for the number of square yards furnished, placed and accepted as determined above at the Contract unit prices for ITEMS 701.050 & 701.150 as set forth in the Bid. Said price and payment shall be full compensation for all finegrading and compacting, for all necessary form work and materials including tactile warning strips and forming of tree wells for future plantings, for furnishing and placing of cement concrete and additives, including fibrous reinforcement and heating charges, for furnishing and applying all curing and/or retarding agents, and for furnishing all tools, equipment, labor, materials, and all else incidental thereto.

701.050	Cement Concrete Sidewalks (4" Fibrous Reinforced)	Square Yards
701.150	Cement Concrete Drives, Aprons and Ramps (6" Fibrous Reinforced)	Square Yards

STONE BOUND REMOVED AND RESET

GENERAL: This work shall consist of resetting existing stone bounds to new lines and grades as required by the OWNER.

MATERIALS: Cement concrete for stone bounds shall be 3000 psi with ¾ inch stone.

METHODS: All excavation shall be done by hand. Prior to excavation at least three accurate ties shall be made to the stone bound, witnessed and approved by the OWNER. Points shall be in locations that will not be disturbed by other construction operations until the bound has been set.

After each stone bound has been set in place and backfilled, the CONTRACTOR will mark the exact survey point in the presence of the OWNER and drill at hole of approximately three-eighth inch diameter to a depth of approximately one-half inch deep.

If, as a result of negligence by the CONTRACTOR, ties are lost or deemed unreliable by the OWNER, it will be the responsibility of the CONTRACTOR to hire a Registered Professional Land Surveyor to conduct a survey to replace such points. The cost of the surveyor and all equipment, materials and manpower shall be paid by the CONTRACTOR at no additional cost to the City.

MEASUREMENT: Measurement for stone bound frame and cover shall be for the number of bounds reset as determined from actual count by the OWNER.

PAYMENT: Payment for stone bounds removed and reset shall be made for the number of stone bounds reset and accepted as determined above at the Contract unit price for ITEM 711.000 as set forth in the Bid. Said price and payment shall be full compensation for all materials including gravel and concrete, for all excavation, backfilling, tools, labor, and all else incidental thereto.

Payment Items

711.000 Stone Bound Removed and Reset Each

STONE BOUND FRAME AND COVER

GENERAL: This work shall consist supplying and installing a cast iron cover over an existing stone bound where there is a change in grade as required by the OWNER.

MATERIALS: Cover shall be S208-6 as supplied by LeBaron Foundry Inc., Brockton, Massachusetts or an approved equal.

METHODS: All excavation shall be done by hand. Covers shall be installed on undisturbed earth with the cover set to the level of the finished grade.

If, as a result of negligence by the CONTRACTOR, the stone bound is moved or broken it shall be the responsibility of the CONTRACTOR to hire a Registered Professional Land Surveyor to conduct a survey to properly locate the stone bound point and the CONTRACTOR shall reset the bound to accurate line and grade. The cost of the replacement, including the surveyor and all equipment, materials and manpower shall be paid by the CONTRACTOR at no additional cost to the City.

MEASUREMENT AND PAYMENT: Measurement for stone bound frame and cover shall be for the number of stone bound frame and cover sets installed and accepted as determined from actual count by the OWNER. Payment for stone bound frame and cover shall be made for the number of stone bound frame and cover sets accepted by the OWNER as determined above at the Contract unit price for ITEM 711.100 as set forth in the Bid. Said price and payment shall be full compensation for all materials, for all excavation, backfilling, tools, labor, and all else incidental thereto.

Payment Items

711.100 Stone Bound Frame and Cover Each

LOAM BORROW

GENERAL: This work shall consist of furnishing and placing loam borrow at the required depths and on approved areas in accordance with these Specifications, as indicated on the Contract Drawings, and/or as required by the OWNER. Only screened loam will be accepted for use.

All grass areas worked on or disturbed during construction and/or grassed areas shown on the Contract Drawings shall be graded to the necessary depths and covered with loam. The loam shall be fertile natural topsoil loam free from brush, weeds, stumps roots, stones over ½ inch in size, and any other objectionable matter. Respreading of existing on-site loam shall be part of ITEM 765.000 and will not be included with as part of this item.

METHOD: In sidewalk loam areas, loam shall be placed and uniformly spread on the sub-grade. When raked out and rolled, the depth of the loam shall be six inches. The finished surface shall be even with the top of the curb and the face of the sidewalk.

If loam is required in adjustment areas, it shall be placed at the depths indicated by the OWNER, but not to exceed 3 inches maximum depth.

MEASUREMENT: Measurement for loam borrow shall be for the number of cubic yards furnished and placed. Measurement shall be made after compaction. This amount shall be measured in the field by the OWNER or, at his option, determined from plan or office calculations. **This shall not include the respreading of any existing on-site loam.** 20% of the measured amount will be added to the final amount to allow for compaction.

PAYMENT: Payment for loam borrow shall be made for the number of cubic yards furnished and placed as determined above at the Contract unit price for ITEM 751.000 as set forth in the Bid. Said price and payment shall be full compensation for furnishing and placing loam borrow to the required depths and limits and for furnishing all tools, labor, equipment, materials, and all else incidental thereto. All work shall be done to the satisfaction of the OWNER. **There will be no separate payment for respreading of existing on-site loam. That shall be considered as part of ITEM 765.000 (SEEDING).**

Cubic Yards	Loam Borrow	751.000
Square Yards	Seeding	765.000
Cubic Yards	Unclassified Excavation	120.100

SEEDING

GENERAL: This work shall consist of the raking, fertilizing, liming, compacting and preparation of loam areas for the furnishing and application of seed. All work shall be done in accordance with these Specifications and/or as required by the OWNER. This item shall also include the respreading of existing on-site loam obtained from stripping operations.

MATERIALS: Lawn seed shall be fresh, clean new crop seed. The seed shall be delivered to the work site with each container bearing the manufacturer's guaranteed analysis. Lawn seed shall be composed substantially as follows and shall be germinative and pure to at least the percentages indicated:

	Proportion	Germinative	Purity
Chewing Fescue or Creeping Red Fescue	25%	85%	97%
Alta Fescue	30%	85%	97%
Domestic Rye Grass	20%	90%	98%
Red Top	15%	90%	92%
White Clover or Alsike	10%	90%	98%

METHOD: The surface to receive seed shall be raked smooth, without pockets, and pleasing to the eye. The area shall be fertilized, limed, seeded, rolled and watered as required to promote satisfactory grass growth. Any areas or parts of areas that fail to show a satisfactory stand of grass within a reasonable amount of time for any reason shall be fertilized and re-seeded until all areas are covered with an adequate acceptable growth of grass. When the grass has grown, the CONTRACTOR shall, at the direction of the OWNER, make a minimum of at least one lawn cutting. Seeding shall be done only within certain times of the year as determined by the OWNER. If seeding is done in the fall season, the acceptance of the work shall not be until the end of the next following growing period. Seed shall be placed at a rate of 2 pounds per 1,000 square feet of area to be covered.

MEASUREMENT: Measurement shall be determined for the number of square yards of area treated and seeded as determined by the OWNER. This amount shall be measured in the field by the OWNER, or, at his option, determined from plan or office calculations.

PAYMENT: Payment for seed shall be made as determined above at the Contract unit price for ITEM 765.000 as set forth in the Bid. Said price and payment shall be full compensation for furnishing and placing all seed, for furnishing and spreading all fertilizer and lime, for raking and compaction of all areas affected, for all cutting, for all tools, labor, equipment, materials and all else incidental thereto. All work is subject to approval by the OWNER. **There will be no payment for respreading of existing on-site loam**. This shall be considered as incidental to the work within this item.

765.000	Seeding	Square Yard
751.000	Loam Borrow	Cubic Yard

3" PVC ELECTRICAL CONDUIT

GENERAL: Furnish and install 3" PVC conduit in locations specified by the OWNER.

MATERIALS: PVC conduit shall be rigid polyvinyl chloride, Schedule 40 as manufactured by Carlon, Phillips Petroleum Co., Triangle Pipe and Tube Co., Inc., or approved equal. Fittings used with PVC conduit shall be PVC and of the same manufacturer as the conduit.

Warning tape shall be 6 inch wide, yellow polyethylene not less than 3.5 mils thick and shall be as manufactured by W. H. Brady Co., Seton Name Plate Co., Unitrust Corp., or approved equal. Warning tape shall display the following message:

CAUTION CAUTION CAUTION BURIED ELECTRIC LINE BELOW

CONSTRUCTION METHODS: Prior to any road construction, the contractor shall check existing conduit in anticipation of installing wires for new cameras. If the contractor is unable to pull wires as required, he shall notify the OWNER who may authorize installation of new conduit.

Underground conduit shall run in straight lines. Where deviation form a straight line becomes necessary, bends shall be of sufficient radius for the proper rodding and installation of cable. Changes in direction of runs exceeding a total of 10 degrees, either vertical or horizontal, shall be made of long sweep bends having a minimum radius of curvature of 25 feet, except that manufactured bends may be used at ends of runs, and then only at or close to the end of the run. The long sweep bends may be made up of one or more curved or straight sections and/or combinations thereof. Manufactured bends shall have a minimum radius of 36 inches where a larger radius cannot be used.

Conduit bends shall be carefully made to prevent distortion of the circular cross-section. No conduit run shall have more than the equivalent of three 90 degrees bends between pulling points. Changes in direction shall be made with bends, standards elbows and pull boxes.

The ends of all conduits shall be tightly plugged during construction until wires are to be pulled. Spare conduits shall be furnished with threaded caps, or removable, neoprene plugs.

Conduit shall be placed on a 6 inch bed of tamped sand.

Do not commence backfilling operations for trenches and structures until all conduit has been installed and approved, and the lengths and locations of all pipe and appurtenances have been recorded. Place an additional 6 inch bed of sand over conduit and backfill, tamping firmly in layers not exceeding six inches, compacting with hand rammers or mechanical tampers

A 2" x 6" untreated wooden plank shall be installed three inches above the conduit. Warning tape shall be installed twelve inches above the plank.

MEASUREMENT AND PAYMENT: Conduit shall be measured in the field prior to backfilling operations. Failure to allow ample time for the Engineer to make the required measurements will

forfeit the Contractor's right-of-claim to any length of conduit other than that allowed by the Engineer. Payment for PVC conduit shall be made for the number of linear feet of conduit installed as determined above at the contract unit price for item 801.300 as set forth in the Bid. Payment shall be full compensation for excavation and backfill; furnishing of tools; hardware; labor; materials including concrete, sand cover and warning tape; equipment; and all else incidental thereto.

Payment Item

801.300 3" PVC Electrical Conduit Linear Feet

LOOP DETECTORS AND LEAD-IN WIRES

GENERAL: This work shall consist of furnishing and installing loop detectors and lead-in wires in areas of resurfacing where the existing loops and lead-ins are removed due to excavation operations. The work shall be done by the CONTRACTOR to the satisfaction of the OWNER.

MATERIALS AND METHODS: The CONTRACTOR shall obtain an electrical permit from the City of Waltham Wire Inspector prior to construction. The CONTRACTOR shall notify the City of Waltham Wire Inspector 60 day's prior to start of work. All traffic signal equipment and related items (such as pavement markings and signs) shall be in place and permission obtained from the City of Waltham Wire Inspector prior to the traffic signal being turned on stop and go operation.

Before starting any installation work, the electrical CONTRACTOR shall furnish data sheets and shop drawings on the materials and methods to be used.

In advance of the loop detector installation, the CONTRACTOR shall mark, on site, the loop detectors with any changes required by field conditions such as manholes. The loop detector layout shall be inspected and approved by the OWNER before the loop detectors are installed.

Loop wire shall be encased in a protected plastic tubing of PVC or polyethylene plastic, IMSA 51-5,0.25 inch outside diameter, and the wire may have cross-linked polyethylene insulation or it may have THHN/THWN insulation.

Splicing insulator shall be an approved re-enterable rigid body splice kit with a non-hardening sealing compound compatible with the wire insulation.

Splice and Connection: Splicing and connection shall be made in the pull box nearest the roadway loop sensor but not exceeding four loops per pull box. All loops included in a detector group as shown on the plans shall be spliced in a single pull box. Each lead and lead-in connector shall be stripped back and spliced using a pressure type wire connector applied with a crimping tool. Multiple loop sensors shall be identified as detailed on the plans.

Lead-in splicing shall be staggered to prevent contact with each other. Each crimped splice shall be soldered and insulated. The insulation material shall be heat-shrinked polyolefin. The shielded lead-in cable outer jacket and shield shall be stripped back sufficiently to ensure that the shield cannot come into contact with the spliced conductors. Follow the instructions of the kit manufacturer for this procedure when installing the re-enterable splice kit.

NOTE WELL: The above splice shall be done on the day of the loop wire installation to prevent the entrance of any moisture into the plastic tubing.

The lead-in conductors shall be connected to the appropriate terminals in the controller cabinet, by using crimped or soldered terminal ends. The heat source for soldering shall be electrical not exceeding 30W capacity.

Testing of Loops: The following test procedure shall be performed in the presence of the OWNER before and after the loop sensor is sealed in the pavement as detailed below. The cost of equipment, labor, and

materials to perform such testing and similar re-testing following repairs, replacement, or adjustment of any detector within the project area shall be included in the contract unit price for this Item.

After installation of wire loop sensors in the roadway and installation of shielded lead-in connecting the loop sensors to the controller cabinet each loop sensor and lead-in combination shall be tested (at the controller cabinet) for proper installation. The resistance from lead to lead of the same loop shall not exceed three ohms per one thousand feet as measured by a high quality meter suitable for measurements of low resistance in the range of 1 to 6 ohms.

A megohm meter test at 500 volts DC shall be made between the two leads of a loop/lead-in combination temporarily spliced together, but otherwise disconnected from all terminals, and the shield drain wire and the earth ground connection. These resistances shall be at least one hundred megohms.

A megohm meter test at 500 volts DC shall be made between lead-in shield and the earth ground rod. This resistance shall be at least one hundred megohms.

The meter used for these tests shall be checked for calibration each day of use by using a resistor block of \pm 5% resistors simulating loads of 1 megohm, 20 megohm and 100 megohms. The observed meter reading shall be \pm 10% of the nominal resistor load.

If any loop sensor and lead-in combination fails to pass any one of the four tests, it shall be repaired and then re-tested on two occasions at least two weeks apart and then shall pass on each re-test occasion. If the loop sensor lead-in combination does not pass all these re-tests, a new loop sensor and/or lead-in shall be installed, and shall pass these tests, at no additional cost.

After the above tests have been satisfactorily completed, all loop sensor/shielded lead-in inductance shall be measured and a written report of the results shall be filed with the OWNER and a copy stored with the "box prints" at the intersection.

MEASUREMENT AND PAYMENT: Measurement for loops furnished, installed and accepted by the OWNER shall be the nominal length of the loop detector and lead-in, not the length of wires. Payment for loop detectors and lead-in wires shall be made as determined above at the contract unit price for ITEM 819.837 as set forth in the Bid. Said price and payment shall be full compensation for furnishing and installing all detectors and lead-ins, all associated materials required, all testing of detectors after installation, and all else incidental thereto to complete the work within this item. All work shall be done to the satisfaction and the approval of the OWNER.

819.837	Loop Detectors with Lead-In Wires	Linear Foot
801.300	3" PVC Electrical Conduit	Linear Feet

TRAFFIC CAMERA

GENERAL: This work shall consist of furnishing and installing traffic cameras on mast arms or traffic light poles in locations specified by the OWNER.

The CONTRACTOR shall obtain an electrical permit from the City of Waltham Wires Inspector prior to construction. The CONTRACTOR shall notify the City of Waltham Wires Inspector 60 days prior to start of work.

EQUIPMENT:

The CMOS Presence Sensor shall be an all-in-one CMOS camera presence sensor. A COD camera shall not be allowed.

The CMOS camera and detection processor shall be contained within a single compact housing. It shall be housed in a discreet and esthetical enclosure of polycarbonate and fiber reinforced polyamide with integrated sunshield/rain visor. The unit dimensions (without mounting bracket) shall be round and no larger than 4' in diameter for minimal EPA impact on existing structures.

The unit shall weigh no more than 22 ounces (including mounting bracket, excluding cabling) for minimal loading impact on existing structures.

The power supply shall accept 12 to 26V AC or DC and the power consumption shall be less than 1.5W. It shall transmit the presence detection information to the traffic controller via four optically isolated open collector outputs. It shall have an RS485 interface for setup.

The unit shall come with a mounting bracket and 4 foot pig tail cable with a military style connector at the end. The unit shall have two available lenses; a 3.5 mm wide angle lens for a detection range of 0 to 80 feet and an 8 mm narrow angle lens for a detection range of 20 to 250 feet.

The unit shall be capable of mounting on mast arms, strain poles or on the tops of pedestal pole mounted signals. The unit shall have an ingress protection rating of IP67. The unit shall operate at a temperature range between -34°C and +80°C.

The unit shall be compliant with CE directive 89/336/EEC; product standard EN55022 class A and EN 50082-2 for Electromagnetic Compatibility (EMC); FCC: FCC part 15 class A; Shock & vibration NEMA II specs.

MEASUREMENT AND PAYMENT: Payment for the traffic camera related equipment will be made at the unit price for ITEM 819.840 as set forth in the Bid. Said price shall be full compensation for furnishing, installation and testing of all equipment, including all labor, tools and materials; for all mounting brackets, connectors and miscellaneous hardware and all else incidental to the satisfactory completion of the work within this item.

819.840	Traffic Camera	Each
801.300	3" PVC Electrical Conduit	Linear Feet
819.850	Traffic Camera Related Equipment	Each
819.860	Sensor Cable	Linear Foot

TRAFFIC CAMERA RELATED EQUIPMENT

GENERAL: This work shall consist of furnishing and installing traffic camera related equipment in locations specified by the OWNER. This item shall include all related equipment need to make the traffic cameras fully operational.

The CONTRACTOR shall obtain an electrical permit from the City of Waltham Wires Inspector prior to construction. The CONTRACTOR shall notify the City of Waltham Wires Inspector 60 days prior to start of work.

EQUIPMENT:

One Sensor Firmware& Software

Sensor firmware & software shall provide presence detection for up to 8 zones. It shall provide video images for the exact positioning of the detection zones. It shall be simple to program via a laptop or ultra-portable PC. It shall provide both non-directional and directional detection in up to 4 directions, user-configured for each zone.

The sensor firmware shall be capable of being upgraded via the PC software. The PC software shall allow for setup of the unit, zone configuration, output assignment, detection verification via refreshing JPEG images (1 detection zone or complete camera image) and the download/upload of configuration data.

The PC software shall run on Windows XP Professional (SP1 and SP2), Windows XP Home, Windows 2000 Professional (SP3), Windows 98(1st and 2nd Editions), Windows NT 4.0 (SP6a) and Windows ME. The software shall require the Java Runtirne Environment Version 1.4.0 or higher and this shall be packaged with the software bundle.

One Quadruple Sensor Controller Interface Module

The controller interface module (CIM) shall be no larger than 3.5"H x 7.5W x 2.5"D and weigh no more than 9oz.The CIM shall be DIN rail mountable. The CIM shall be able to interface to up to 4 CMOS presence sensors. One shall be required for up to 4 sensors. The CIM shall have sixteen green LED detection output indicators. The CIM shall provide optical isolation. The CIM shall have integral terminal blocks for power input, power output (to sensor) RS486 (from sensor), 16 detection outputs + common (to controller), one general error output + reference (to controller) and Shielding/Earth Ground.

The CIM shall have a USB port for the USB interface. The CIM housing shall be plastic. EMC: CE directive 891336/EEC; product standard EN55022 class A. FCC: FCC part 15 class A. Shock & vibration NEMA II specifications.

One Cabinet Mount Detector Interface

Where applicable, a shelf mount detector interface shall be installed in the cabinet. This interface shall allow the use of the existing shelf mount loop detector harness to facilitate communications from the CIM to the traffic controller. It shall have and military style connectors to match that of the shelf mount detector harness.

One Sensor Mounting Hardware

The mounting bracket shall be made from fiber reinforced polyamide. The mounting bracket shall be capable of being banded to a horizontal or vertical pole. The mounting bracket shall provide for at least 2 axes of rotational adjustment: pan and tilt.

One Ultra-Portable PC Configuration

Ultra-Portable Tablet PC with 512MB RAM, 40GB Hard drive. Windows XP Tablet Edition. 7" WVGA Widescreen Active Matrix TFT LCD Touch Screen or approved equal.

MEASUREMENT AND PAYMENT: Payment for the traffic camera related equipment will be made at the contract unit price for ITEM 819.850 as set forth in the Bid. Said price shall be full compensation for furnishing, installation and testing of all equipment, including all labor, tools and materials; for all mounting brackets and miscellaneous hardware and all else incidental to the satisfactory completion of the work within this item.

819.850	Traffic Camera Related Equipment	Linear Feet
801.300	3" PVC Electrical Conduit	Linear Feet
819.840	Traffic Camera	Each
819.860	Sensor Cable	Linear Foot

SENSOR CABLE

GENERAL: This work shall consist of furnishing and installing traffic camera sensor cable in locations specified by the OWNER.

The CONTRACTOR shall obtain an electrical permit from the City of Waltham Wires Inspector prior to construction. The CONTRACTOR shall notify the City of Waltham Wires Inspector 60 days prior to start of work.

EQUIPMENT: The sensor cable shall be housed within a single overall jacket. The sensor cable shall consist of two 22AVVG twisted pairs: one 22AWG twisted pair for RS485 communications and one 22AWG twisted pair for power (i.e. in total 4 wires plus shielding). The 22AWG twisted pairs shall be 7 stranded tinned copper and overall shielding. The 22AWG paired color coding shall be Green/Yellow for RS485 and Blue/Red for power. The 22AWG twisted pair shield shall be an alum poly foil with 100% coverage and the drain wire shall be 24AWG 7 strand tinned copper. The insulation thickness shall be 0.010". The cable shall be rated for 300V and -20 to 90 Degrees Celsius. The overall jacket shall be a 0.032" black PE with a nominal diameter of 0.25". There shall be a 4 foot pig tail at the CMOS camera with a military style connector on the opposite end of the CMOS camera. This MS connector shall be weatherproof.

MEASUREMENT AND PAYMENT: Payment for Sensor Cable will be made at the contract unit price for ITEM 819.860 as set forth in the Bid. Said price shall be full compensation for furnishing, installation and testing of all equipment, including all labor, tools and materials; miscellaneous hardware and all else incidental to the satisfactory completion of the work within this item.

819.860	Sensor Cable	Linear Foot
801.300	3" PVC Electrical Conduit	Linear Foot
819.840	Traffic Camera	Each
819.850	Traffic Camera Related Equipment	Lump Sum

SAFETY SIGNING FOR CONSTRUCTION OPERATIONS

GENERAL: This work shall consist of furnishing, installing, maintaining, repositioning, removing and storing temporary signs for the protection of the traveling public and working personnel during construction and maintenance operations. The design, application and installation of such signs shall comply with the Massachusetts Manual on Uniform Traffic Control Devices, latest edition. All materials provided by the CONTRACTOR under this item shall remain the property of the CONTRACTOR upon completion of this project.

MATERIALS AND METHODS: Materials required under this section need not be new but must be in excellent condition. Any materials that in the judgment of the OWNER are unsatisfactory in appearance or performance shall be removed and immediately replaced by acceptable units at no additional cost to the City. Signs that are missing shall be immediately replaced by the CONTRACTOR at no additional cost to the City. Signs that are not consistent with the use of the roadway shall be removed or covered. All work shall be done by the CONTRACTOR and to the satisfaction of the OWNER.

Materials shall conform to Sections 828 and 840 of the Commonwealth of Massachusetts Standard Specifications except the plywood material shall conform to the following: Plywood sign panels shall be fabricated from five-ply 5/8"thick Medium Density Overlaid Exterior Type, A-B both sides surface in natural color and the whole conforming with the requirements and tests for the above as set forth in U. S. product Standard PS1-74 for Construction and Industrial Plywood. Plywood shall bear the grade trade mark of an approved testing agency. The entire sign face shall be reflectorized with reflective sheeting conforming to M9.30.0, type III of the Commonwealth of Massachusetts Standard Specifications.

Background sheeting shall be fluorescent orange. The maximum spectral radiance factor, in accordance with Section 5.1 of ASTM E991 for the fluorescence shall be 110% minimum for new signs and 60% minimum for weathered signs. Actual size and legend shall be determined by the OWNER.

MEASUREMENT: Measurement for safety signing shall be based on the square foot surface area of the signs. All measurements for safety signing shall be made in the field by the OWNER. **Sign supports for safety signing are considered incidental to installation of the signs and there shall be no additional payment.**

PAYMENT: Payment for Safety Signing for Construction Operations shall be made based on the square foot area as determined above at the Contract unit price for ITEM 850.221 as set forth in the Bid. Said

price and payment shall be full compensation for furnishing, maintaining, repositioning, removing and storing signs, including all labor, equipment, tools, cement concrete, if required, and all else incidental to the satisfactory completion of the work within this item. All work is subject to approval by the OWNER.		
	Payment Items	
850.221	Safety Signing for Construction Operations	Square Foot

4" TEMPORARY PAINTED LINE

GENERAL: This work shall including temporary paint for traffic control following cold planing in locations required by the OWNER. The work to be done under these items shall conform to the relevant provisions of Section 860 of the 1988 MDPW Standard Specifications for Highways and Bridges, and the following:

METHODS: The layout shall be approved by the OWNER. Application shall be sufficient to last until the wearing course of pavement has been applied.

MEASUREMENT: Measurement for temporary painted lines shall be for the actual number of linear feet furnished and installed by the CONTRACTOR and accepted by the OWNER.

PAYMENT: Payment for temporary painted lines shall be for the actual linear feet as determined above at the contract unit price for ITEM 854.014 as set forth in the Bid. Said price and payment shall be full compensation for furnishing and placing of all materials, all tools, labor, equipment and all else incidental to the completion of the work. All work is subject to final approval and acceptance by the OWNER.

Payment Items

854.014 4" Temporary Painted Line Linear Foot

GENERAL: The work to be done under these items shall conform to the relevant provisions of Section 860 of the 1988 MDPW Standard Specifications for Highways and Bridges, and the following:

METHODS: The layout of all necessary field controls by the CONTRACTOR of the several types of traffic line systems shall be approved by the OWNER. The width and spacing of stop lines and crosswalks shall be as indicated on the plans.

MEASUREMENT: Measurement for pavement arrows, legends, crosswalks, stop lines, chevrons and/or gore lines shall be for the actual square foot of area of material furnished and installed by the CONTRACTOR and accepted by the OWNER. Measurement for other thermoplastic lines shall be for the actual linear foot of material furnished and installed by the CONTRACTOR and accepted by the OWNER. All measurement shall be done in the field by the OWNER.

PAYMENT: Payment for arrows, legends, crosswalks, stop lines, chevrons and/or gore lines shall be for the actual square foot area as determined above at the contract unit prices for ITEMS 864.040 and 865.100 as set forth in the Bid. Payment for other thermoplastic markings shall be for the actual linear foot measurement as determined above at the contract unit prices for ITEMS 868.040 and 868.020 as set forth in the Bid. Said price and payment shall be full compensation for furnishing and placing of all materials, all tools, labor, equipment and all else incidental to the completion of the work within these items. All work is subject to final approval and acceptance by the OWNER.

864.040	Pavement Arrows and Legends Reflectorized Thermoplastic	Square Foot
865.100	X - Walks and Stop Lines Reflectorized White (Thermoplastic)	Square Foot
868.040	4" Reflectorized Thermoplastic Line	Linear Foot

PORTABLE MESSAGE BOARD

GENERAL: Portable message boards shall conform to the relevant provisions of Section 6F.52 of the Federal Highway Administration Manual on Uniform Traffic Devices. Message boards shall be solar powered, capable for displaying three alternating messages of three lines, eight characters per line.

MEASUREMENT AND PAYMENT: Measurement for each Portable Message Board shall be per day whenever boards are required and accepted by the OWNER. Payment for Portable Message Boards shall be as determined above at the contract unit prices for ITEM 870.000 as set forth in the Bid. Said price and payment shall be full compensation for furnishing equipment and programming, locating and relocating message boards as required by the OWNER. All work is subject to final approval and acceptance by the OWNER.

Payment Items

870.000 Portable Message Board DAY

TRAFFIC POLICE

GENERAL: The CONTRACTOR shall provide such uniformed police officers (outside their regular tour of duty) as the OWNER shall deem necessary to avoid, so far as reasonably possible, damage to the safety of persons and substantial interference with the free circulation of traffic. When so required by the OWNER, the CONTRACTOR shall make all arrangements in obtaining police assistance. The CONTRACTOR shall pay the amount due for such assistance to the City of Waltham. The CONTRACTOR shall then be reimbursed by the City of Waltham. Police details may be arranged by calling (781) 314-3604.

All bills for police details must be paid in full by the CONTRACTOR before reimbursement is made by the City of Waltham. Only bills stamped "PAID" by the City Treasurer's Office will be accepted by the OWNER.

METHOD OF PAYMENT: The CONTRACTOR shall pay to any police officer employed by him the prevailing rate of wage to special duty police officers (MGL Chapter 149, §34B). The quantity on the Bid form for ITEM 999.001 is an estimate for funding and bid comparison purposes. Payment to the CONTRACTOR for special duty police will be made at the rate established by the Waltham Police Department.

Payment shall be made by the CONTRACTOR within 30 days of billing. Failure to pay an outstanding bill within 30 days may result in a penalty charge to the CONTRACTOR for late payment. There will be no reimbursement for any penalties or late charges that may be assessed against the CONTRACTOR for late payment. Furthermore, the OWNER will accept no further requests for payment if police detail bills are more than 30 days in arrears.

The CONTRACTOR will not be reimbursed for any detail that he fails to cancel when it is not required (work does not proceed as scheduled or due to inclement weather, etc.) Reimbursement will be entered in the next estimate for payment.

Reimbursement shall be made on all bills stamped "PAID" by the City of Waltham Treasurer's Office and presented to the OWNER less any amount for unnecessary details not canceled by the CONTRACTOR when required.

It is suggested that payments be made in person at the Treasurer's Office and that a copy of the bill be presented to the Treasurer's Office at the same time so that it may be stamped "PAID" and presented to the OWNER by the CONTRACTOR.

PAYMENT: Payment for special duty police will be made on a dollar for dollar basis as determined above for ITEM 999.001 as set forth in the Bid. Said price and payment shall be full compensation for furnishing all special duty police.

Payment Item

999.001 Traffic Police Per Dollar

	8 - MISCELLANEOUS DETAIL DRAWINGS	
	AND DOCUMENTS	
	FOR	
	ANNUAL CONTRACT FOR	
DE	ANNUAL CONTRACT FOR	
RE	ANNUAL CONTRACT FOR ESURFACING OF BITUMINOUS ROADWAYS AND REPAIRS TO SIDEWALKS	
RE		